



PRODUCT-DETAILS

CM-TCN.011P

CM-TCN.011P Temp. monitoring relays LCD+NFC, -200..+850°C, 24-240VAC/DC



General Information

Extended Product Type	CM-TCN.011P
Product ID	1SVR760740R0110
EAN	4013614552625
Catalog Description	CM-TCN.011P Temp. monitoring relays LCD+NFC, -200..+850°C, 24-240VAC/DC

Long Description	<p>The CM-TCN.011P is an innovative temperature monitoring relay from the CM temperature monitors range. This monitoring relay operates with a rated control supply voltage of 24 - 240 V AC / DC and has a 3 c/o (SPDT) output with contacts rated at 250 V / 4 A. The CM-TCN.011P is able to measure temperatures with up to three sensor circuits using different type of sensors PT100, PT1000, PTC or NTC. The LCD at the front of the relay shows the currently measured values and maintenance data. The CM-TCN.011P can be configured exactly as you need either via a black-lit LCD or smartphone app. Parametrization and configuration are just one touch away with the ABB EPiC app - even in a non-powered state - reducing installation time by 80%. The device offers maintenance free Easy Connect Technology with push-in terminals.</p>
------------------	---

Ordering

EAN	4013614552625
Minimum Order Quantity	1 piece
Customs Tariff Number	85364900

Popular Downloads	
Data Sheet, Technical Information	2CDC112286C0201
Instructions and Manuals	1SVC750040M0000 2CDC112285M0201
CAD Dimensional Drawing	2CDC001079B0201

Dimensions	
Product Net Width	45 mm
Product Net Height	85.6 mm
Product Net Depth / Length	103.7 mm
Product Net Weight	0.265 kg

Technical	
Function	Overtemperature monitoring Undertemperature monitoring Over- and undertemperature monitoring
Measuring Range	-200 ... +850 °C
Sensor Type	PT100; PT1000; PTC; NTC; bimetal switch
Rated Control Supply Voltage (U _s)	24 ... 240 V AC/DC
Rated Frequency (f)	Supply Circuit 50 Hz Supply Circuit 60 Hz Supply Circuit DC Hz
Output	3 x 1 c/o contacts, configurable
Terminal Type	Screwless Terminals
Rated Operational Current AC-12 (I _θ)	(230 V) 4 A
Rated Operational Current AC-15 (I _θ)	(230 V) 3 A
Rated Operational Current DC-12 (I _θ)	(24 V) 4 A
Rated Operational Current DC-13 (I _θ)	(24 V) 2 A
Minimum Switching Capacity	12 V 100 mA
Rated Impulse Withstand Voltage (U _{imp})	Measuring Circuit / Output Circuit 6 kV Output Circuit 1 / Output Circuit 2 4 kV Supply Circuit / Measuring Circuit 6 kV Supply Circuit / Output Circuit 6 kV
Rated Insulation Voltage (U _i)	Measuring Circuit / Output Circuit 600 V Output Circuit 1 / Output Circuit 2 300 V Supply Circuit / Measuring Circuit 600 V Supply Circuit / Output Circuit 600 V
Degree of Protection	Housing IP50 Terminals IP20
Overvoltage Category	III
Pollution Degree	2
Short-Circuit Protective Devices	Output Circuit NC - F Type Fuses 6 A Output Circuit NO - F Type Fuses 10 A
Electrical Durability	AC-12 100000 cycle
Mechanical Durability	30000000 cycle
Connecting Capacity	Flexible with Ferrule 2x 0.5 ... 1.5 mm² Flexible with Insulated Ferrule 2x 0.5 ... 1.5 mm² Flexible 2x 0.5 ... 1.5 mm² Rigid 2x 0.5 ... 1.5 mm²
Wire Stripping Length	8 mm
Mounting Position	1 ... 6
Mounting on DIN Rail	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715

TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715

Technical UL/CSA

Maximum Operating Voltage UL/CSA	Output Circuit 300 V AC
Contact Rating UL/CSA	B300
Connecting Capacity UL/CSA	Flexible 2x 18-16 AWG Rigid 2x 20-16 AWG
Pilot Duty UL/CSA	B300

Environmental

Ambient Air Temperature	Operation -25 ... +60 °C Storage -40 ... +85 °C
Maximum Operating Altitude Permissible	Without Derating 2000 m

Material Compliance

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	1SVD981001-4501
RoHS Information	1SVD981001-4401
RoHS Status	Following EU Directive 2011/65/EU
Toxic Substances Control Act - TSCA	2CMT2023-006536

Circular Value

Environmental Information	1SAC200220H0001
---------------------------	-----------------

Certificates and Declarations

CQC Certificate	CQC2018010303056014
CSA Certificate	UL-CA-L140448-41-22600202-1
Declaration of Conformity - CCC	2020980303000208
Declaration of Conformity - CE	1SVD981067-00
Declaration of Conformity - UKCA	1SVD981067-10
UL Certificate	UL-US-L140448-11-22600202-1

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	97 mm
Package Level 1 Depth / Length	52.5 mm
Package Level 1 Height	109 mm
Package Level 1 Gross Weight	0.293 kg
Package Level 1 EAN	4013614552625

Classifications

Object Classification Code		B
ETIM 7	EC001446 - Temperature monitoring relay	
ETIM 8	EC001446 - Temperature monitoring relay	
ETIM 9	EC001446 - Temperature monitoring relay	
eClass	V11.0 : 27371810	
UNSPSC	39122331	

Categories

Low Voltage Products and Systems → Control Products → Electronic Relays and Controls → Temperature Monitors

