FCC/S1.1.1.1 1/3



PRODUCT-DETAILS

FCC/S1.1.1.1

FCC/S1.1.1.1 Fan Coil Controller, 2 x PWM, 3-stage, MDRC



EAN	4016779011426
Product ID	2CDG110210R0011
Extended Product Type	FCC/S1.1.1.1

Catalog Description

FCC/S1.1.1.1 Fan Coil Controller, 2 x PWM, 3-stage, MDRC
For the control of fan coil units. Via two electronic outputs, two thermoelectric or one motor-

driven valve drive can be controlled for heating and cooling. For the fan control the devices features three relay outputs. A relay output switches an additional load of up to 16 A, such as auxiliary heating. Over 4 inputs the room status can be detected and monitored (Use for window contact, dew point sensor, level sensor or temperature sensor). Also it is possible to connect one analog room control unit (SAR/A or SAF/A) to the inputs of the device. The device has an integrated room temperature controller for the control of the room temperature, which can be used directly to control the outputs of the device. The device

supports the ABB i-bus Tool for advanced diagnosis and improved commissioning.

Long Description

Installation

Instructions and Manuals

Mounting Type

2CDG941188P0002

DIN-Rail

Technical

FCC/S1.1.1.1 2/3

Data Sheet, Technical	2CDC508212D0211			
Information	W. B. de			
Special Functions	Valve Protection			
Number of Outputs	<u>5</u>			
Number of Digital Inputs				
Number of Inputs	Analog (0 10 V / 4 20 mA) 4			
Compatible Bus Systems Product Range	KNX (TP) KNX			
Manual Operation	No			
Number of Batteries	0			
Number of Butteries	<u> </u>			
Electrical				
Maximum Switching Current	16 A			
Output Current Maximum (I _{out})	0.5 A			
Power Loss	3 W			
Design				
Color	light grey			
Soloi	ight diey			
Material Compliance				
RoHS Information	2CDK508221D2701			
RoHS Status	Following EU Directive 2011/65/EU			
REACH Declaration	9AKK108468A9644			
REACH Information	False - does not contains substances > 0.1 mass percentage			
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363			
, comitty				
Environmental				
Degree of Protection	IP20			
Dimensions				
Width in Number of Modular Spacings	6			
Product Net Width	105 mm			
Product Net Height	90 mm			
Product Net Depth / Length	63.5 mm			
Product Net Weight	0.23 kg			
Dimension Diagram	2CDC072026F0017			
Certificates and Declarations				
CB Certificate	9AKK107991A3187			
Declaration of Conformity	2CDK508221D2701			
<u>- CE</u>				

FCC/S1.1.1.1 3/3

Classifications	
ETIM 9	EC001586 - Heating actuator for bus system
eClass	V11.0 : 27143147
UNSPSC	39121801
Object Classification Code	A
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer

Accessories				
Identifier	Description	Туре	Quantity	Unit Of Measure
2CDG120049R0011	TSA/K230.2 Thermoelectric Valve Drive, 230 V	TSA/K230.2	1	piece
2CDG120050R0011	TSA/K24.2 Thermoelectric Valve Drive, 24 V	TSA/K24.2	1	piece
2CKA006134A0346	SAR/A1.0.1-24 RT-control element S	AR/A1.0.1-24	1	piece
2CKA006134A0348	SAF/A1.0.1-24 HVAC-control element S	SAF/A1.0.1-24	1	piece

Categories

 $\mbox{Low Voltage Products and Systems} \rightarrow \mbox{Building and Home Automation Solutions} \rightarrow \mbox{KNX} \rightarrow \mbox{Heating, Ventilation and Air Conditioning} \rightarrow \mbox{Fan Coil Controllers}$









3605