HCC/S2.2.2.1 1/3



PRODUCT-DETAILS

## HCC/S2.2.2.1

## HCC/S2.2.2.1 Heating/Cooling Circuit Controller, 2-f, 3-point, Man Op, MDRC



<b>General Information</b>	
Extended Product Type	HCC/\$2.2.2.1
Product ID	2CDG110221R0011
EAN	4016779011648
Catalog Description	HCC/S2.2.2.1 Heating/Cooling Circuit Controller, 2-f, 3-point, Man Op, MDRC
Long Description	For the control of a heating or cooling circuit. The device has 2 channels, each with two electronic outputs to control a motor-driven mixing valve (3-Point) of a heating or cooling circuit as well as a relay output (5A) to switch the pump of the circuit. Via 3 binary inputs it is possible to monitor the status of the pump (via potential free contacts) and integrate these feedback into the control of the pump. The flow and return flow temperature are measured and used for the calculation of the control value for the valve output in the integrated controller. The set point temperature is received via the KNX bus. By bundling both channels of the device it is also possible to use it for double pump systems  The HCC/S 2.2.2.1 features an easy to use manual operation.  The device supports the ABB i-bus Tool for advanced diagnosis and improved commissioning.

Instructions and 2CDG941187P0003
Manuals

HCC/S2.2.2.1 2/3

Mounting Type DIN-Rail

Technical	
Data Sheet, Technical Information	2CDC508249D0211
Special Functions	Valve Protection
Number of Outputs	4
Number of Digital Inputs	10
Number of Inputs	Analog (0 10 V / 4 20 mA) 10
Compatible Bus Systems	KNX (TP)
Manipulated Variable	Continious
Product Range	KNX
Manual Operation	Yes
Number of Batteries	0

Electrical	
Voltage Range	24 230 V AC/DC
Maximum Switching Current	5 A
Output Current Maximum (I <sub>out</sub> )	0.5 A
Power Loss	3 W

Design	
Color	light grey

Material Compliance	
RoHS Information	2CDK508233D2701
RoHS Status	Following EU Directive 2011/65/EU
REACH Declaration	9AKK108468A9644
REACH Information	False - does not contains substances > 0.1 mass percentage
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Environmental	
Degree of Protection	IP20

Dimensions	
Width in Number of Modular Spacings	8
Product Net Width	140 mm
Product Net Height	90 mm
Product Net Depth / Length	63.5 mm
Product Net Weight	0.29 kg

HCC/S2.2.2.1 3/3

Dimension Diagram 2CDC072027F0017

Certificates and Declarations	
CB Certificate	9AKK107991A3190
Declaration of	2CDK508233D2701
Conformity - CE	

Classifications	
ETIM 9	EC001586 - Heating actuator for bus system
eClass	V11.0 : 27143147
UNSPSC	39121801
Object Classification Code	А
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer

## **Categories**

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Building\ and\ Home\ Automation\ Solutions \rightarrow KNX \rightarrow Heating,\ Ventilation\ and\ Air\ Conditioning \rightarrow Central\ HVAC\ Controllers$ 









3605