




PRODUCT-DETAILS

# SAH/S16.6.7.1

## SAH/S16.6.7.1 Switch/Shutter Actuator, 16-fold, 6 A, MDRC



General Information	
Extended Product Type	SAH/S16.6.7.1
Product ID	2CDG110245R0011
EAN	4016779066792
Catalog Description	SAH/S16.6.7.1 Switch/Shutter Actuator, 16-fold, 6 A, MDRC
Long Description	The compact 6 A combi switch actuator has 16 independent switching relays. The outputs can be used individually via ABB i-bus® KNX for switching electrical loads or in pairs for controlling 230 V AC roller shutter or blind drives (no electromechanically interlocking). The device features a manual operation, which can also be disabled. Via the manual operation the outputs can be operated manually and the switching or driving status is displayed. The device is powered by KNX and requires no additional power supply.
Installation	
Instructions and Manuals	2CDG941210P0002
Mounting Type	DIN-Rail
Technical	
Data Sheet, Technical Information	2CDC505176D0211

Contact Position Indication	ON / OFF
Number of Outputs	16
Number of LEDs	10
Maximum Number of Switching Outputs	16
Compatible Bus Systems	KNX (TP)
Product Range	KNX
Manual Operation	Yes
Suitable for C-Load	No
Number of Batteries	0

Electrical

Voltage Range	230 V AC
Auxiliary Voltage AC/DC	KNX
Output Voltage (U <sub>out</sub> )	230 V AC
Rated Current (I <sub>n</sub> )	6 A
Maximum Switching Current	6 A
Maximum Switching Power	1200 W
Power Loss	5 W

Design

Color	light grey
-------	------------

Material Compliance

RoHS Information	2CDK505207D2701
RoHS Status	Following EU Directive 2011/65/EU
REACH Declaration	9AKK108468A9644
REACH Information	False - does not contains substances > 0.1 mass percentage
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363
SCIP	5043cba7-df94-434c-b7cb-211cb48d9eca Germany (DE)

Environmental

Ambient Air Temperature	Operation -5 ... +45 °C
Degree of Protection	IP20

Dimensions

Width in Number of Modular Spacings	8
Product Net Width	140 mm
Product Net Height	90 mm
Product Net Depth / Length	63.5 mm
Product Net Weight	0.502 kg
Built-In Depth (t <sub>2</sub> )	63.5 mm
Dimension Diagram	2CDC072027F0017

Certificates and Declarations

CB Certificate	9AKK107991A3222
Declaration of Conformity	2CDK505207D2701
- CE	

Classifications

ETIM 9	EC001097 - Switch actuator for bus system
eClass	V11.0 : 27143125
UNSPSC	31251516
IDEA Granular Category Code (IGCC)	3268 >> Switch actuator
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer

Categories

Low Voltage Products and Systems → Building and Home Automation Solutions → KNX → Standard Outputs → Switch Actuators 6 A



365