SA/S12.6.2.2 1/3



PRODUCT-DETAILS

SA/S12.6.2.2

SA/S12.6.2.2 Switch Actuator, 12-fold, 6 A, MDRC



Extended Product Type	SA/S12.6.2.2
Product ID	2CDG110256R0011
EAN	4016779066778
Catalog Description	SA/S12.6.2.2 Switch Actuator, 12-fold, 6 A, MDRC
Long Description	The switch actuator uses potential free contacts to switch 12 independent electrical loads via the ABB i-bus® KNX. The device features a manual operation and displaying of the switching state of the outputs. The 6 A device is especially suited to switch resistive, inductive or capacitive loads. The device is powered by KNX and requires no additional power supply.
Installation	
Installation Instructions and Manuals	2CDG941213P0001

Technical

Data Sheet, Technical

Information
Contact Position

2CDC505187D0211

ON / OFF

SA/S12.6.2.2 2/3

Indication	
Indication Number of Outputs	12
Number of LEDs	
Maximum Number of	12
Switching Outputs	12
Compatible Bus Systems	KNX (TP)
Product Range	KNX
Manual Operation	No
Suitable for C-Load	No
Number of Batteries	0.
Electrical	
Voltage Range	230 V AC
Auxiliary Voltage AC/DC	KNX
Output Voltage (U _{out})	230 V AC
Rated Current (I _n)	6 A
Maximum Switching Current	6 A
Maximum Switching Power	1380 W
Power Loss	3.9 W
Design	
Color	light grey
Material Compliance	
RoHS Information	2CDK505259D2701
RoHS Status	Following EU Directive 2011/65/EU
REACH Declaration	9AKK108468A9644
REACH Information	False - does not contains substances > 0.1 mass percentage
Conflict Minerals Reporting Template	9AKK108468A3363
(CMRT) SCIP	6b543a96-0a33-4c04-acc7-93b50e9e318a Germany (DE)
<u>5611</u>	obstatio-data-accr-subsideses for definiting (DE)
Environmental	
Environmental Ambient Air Temperature	Operation 5 ±45 °C
Ambient Air Temperature	Operation -5 +45 °C
	Operation -5 +45 °C IP20
Ambient Air Temperature Degree of Protection	
Ambient Air Temperature Degree of Protection Dimensions Width in Number of	
Ambient Air Temperature Degree of Protection Dimensions Width in Number of Modular Spacings	1P20 12
Ambient Air Temperature Degree of Protection Dimensions Width in Number of Modular Spacings Product Net Width	12 210 mm
Ambient Air Temperature Degree of Protection Dimensions Width in Number of Modular Spacings Product Net Width Product Net Height	12 210 mm 90 mm
Ambient Air Temperature Degree of Protection Dimensions Width in Number of Modular Spacings Product Net Width	12 210 mm
Ambient Air Temperature Degree of Protection Dimensions Width in Number of Modular Spacings Product Net Width Product Net Height Product Net Depth /	12 210 mm 90 mm
Ambient Air Temperature Degree of Protection Dimensions Width in Number of Modular Spacings Product Net Width Product Net Height Product Net Depth / Length	12 210 mm 90 mm 63.5 mm
Ambient Air Temperature Degree of Protection Dimensions Width in Number of Modular Spacings Product Net Width Product Net Height Product Net Depth / Length Product Net Weight	12 210 mm 90 mm 63.5 mm 0.608 kg

SA/S12.6.2.2 3/3

Ordering	
Replaced Product ID (OLD)	2CDG110183R0011

Certificates and Declarations		
CB Certificate	9AKK107991A3224	
Declaration of Conformity - CE	2CDK505259D2701	

Classifications	
ETIM 9	EC001097 - Switch actuator for bus system
eClass	V11.0 : 27143125
UNSPSC	31251516
IDEA Granular Category Code (IGCC)	3268 >> Switch actuator
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Building\ and\ Home\ Automation\ Solutions \rightarrow KNX \rightarrow Standard\ Outputs \rightarrow Switch\ Actuators\ 6\ Angles \ Angl$









360