SA/S2.16.6.2 1/4



PRODUCT-DETAILS

SA/S2.16.6.2

SA/S2.16.6.2 Switch Actuator, 2-fold, 16 A, C-Load, Energy Function, MDRC



General Information	
Extended Product Type	SA/S2.16.6.2
Product ID	2CDG110269R0011
EAN	4016779066327
Catalog Description	SA/S2.16.6.2 Switch Actuator, 2-fold, 16 A, C-Load, Energy Function, MDRC
Long Description	The switch actuator uses potential free contacts to switch 2 independent electrical loads via ABB i-bus® KNX. The device has integrated energy functions. This includes independent load current measurement in each output and easy to use calculation of power and energy consumption for each output or groups of outputs. Via an integrated load shedding object an integration in a load control system can be easily realized. The device features a manual operation and displaying of the switching state of the outputs. The 16/20 A, 16 A-AC3 (C-load) device is especially suited for loads with high surge currents e.g. LED or fluorescent lighting (AX) acc. EN60669.

Installation	
Instructions and Manuals	2CDG941217P0002
Mounting Type	DIN-Rail

SA/S2.16.6.2 2/4

Technical	
Data Sheet, Technical Information	2CDC505200D021
Contact Position Indication	ON / OF
Number of Outputs	
Number of LEDs	
Maximum Number of Switching Outputs	
Compatible Bus Systems	KNX (TP
Product Range	KN
Manual Operation	N
Suitable for C-Load	Ye
Number of Batteries	
Electrical	
Voltage Range	230 V A(
Auxiliary Voltage AC/DC	KN
Output Voltage (U _{out})	230 V A(
Rated Current (I _n)	20 /
Maximum Switching Current	20 /
Maximum Switching Power	3680 V
Power Loss	2 V
Design	
Color	light gre
 Material Compliance	
·	200//5552450272
RoHS Information	2CDK505246D270
REACH Declaration	Following EU Directive 2011/65/EU 9AKK108468A964
REACH Information	False - does not contains substances > 0.1 mass percentag
Conflict Minerals Reporting Template	9AKK108468A336
(CMRT) SCIP	08398a39-6e6d-4088-9c2a-35cf7ba67472 Germany (DE
SCIP	00390d39-0e00-4000-9C2d-33C11Dd01412 GeITId1ly (DE
Environmental	
Ambient Air Temperature	Operation -5 +45 °(
Degree of Protection	IP2·
Dimensions	
Width in Number of	
Modular Spacings	

SA/S2.16.6.2 3/4

Product Net Width	36 mm
Product Net Height	90 mm
Product Net Depth / Length	63.5 mm
Product Net Weight	0.169 kg
Built-In Depth (t ₂)	64.5 mm
Dimension Diagram	2CDC072025F0017

Ordering

Replaced Product ID	2CDG110112R0011
(OLD)	

Certificates and Declarations

CB Certificate	9AKK107991A3225
Declaration of	2CDK505246D2701
Conformity - CE	

Classifications

Classifications	
ETIM 9	EC001097 - Switch actuator for bus system
eClass	V11.0 : 27143125
UNSPSC	31251516
IDEA Granular Category Code (IGCC)	3268 >> Switch actuator
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Building\ and\ Home\ Automation\ Solutions \rightarrow KNX \rightarrow Standard\ Outputs \rightarrow Switch\ Actuators\ 16/20\ A$

SA/S2.16.6.2 4/4









360