



PRODUCT-DETAILS

BCM/S6.5.5.1

BCM/S6.5.5.1 BAC Module, 4 Analogue Inputs and 2 Analogue Outputs



General Information	
Extended Product Type	BCM/S6.5.5.1
Product ID	2CDG120067R0011
EAN	4016779064453
Catalog Description	BCM/S6.5.5.1 BAC Module, 4 Analogue Inputs and 2 Analogue Outputs
Long Description	Extension module for the BAC/S Building Automation Controller KNX with 4 analog inputs and 2 analog outputs. The inputs and outputs support voltage signals from 0 V ... + 10 V, 0 V ... + 5 V, -2.5 V ... + 2.5 V and -5 V ... + 5 V as well as current signals of 0 mA ... 20 mA and 4 mA ... 20 mA. Connection of the cables via pluggable spring terminals.
Installation	
Instructions and Manuals	9AKK107046A7504
Mounting Type	DIN-Rail
Technical	

Data Sheet, Technical Information	9AKK107046A7504
Number of Outputs	2
Number of Inputs	Analog (0 ... 10 V / 4 ... 20 mA) 4
Product Range	KNX
Manual Operation	No
Number of Batteries	0

Electrical

Auxiliary Voltage AC/DC	24 V DC
Output Voltage (U _{out})	0 ... 10 V DC
Power Loss	4.9 W

Design

Color	grey
-------	------

Material Compliance

RoHS Status	No declaration needed
REACH Declaration	9AKK108468A9644
REACH Information	False - does not contains substances > 0.1 mass percentage
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Environmental

Degree of Protection	IP20
----------------------	------

Dimensions

Product Net Width	34 mm
Product Net Height	135 mm
Product Net Depth / Length	74 mm
Product Net Weight	0.18 kg

Certificates and Declarations

Declaration of Conformity - CE	9AKK107046A7504
--------------------------------	-----------------

Classifications

ETIM 9	EC001420 - PLC analogue I/O-module
eClass	V11.0 : 27242201
UNSPSC	32151705
Object Classification Code	A

WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer

Categories

Low Voltage Products and Systems → Building and Home Automation Solutions → KNX → Heating, Ventilation and Air Conditioning → Central HVAC Controllers

