SDA-F-1.1.PB.1-WL 1/3



PRODUCT-DETAILS

## **SDA-F-1.1.PB.1-WL**

## SDA-F-1.1.PB.1-WL WL-Sens./ Dimact. 1/1, 44



General Information	
Extended Product Type	SDA-F-1.1.PB.1-WL
Product ID	2CKA006200A0111
EAN	4011395216002
Catalog Description	SDA-F-1.1.PB.1-WL WL-Sens./ Dimact. 1/1, 44
Long Description	For dimming 230 V~ loads. Communication with the free@home system is carried out wireless. With integrated universal dimming actuator for controlling LEDs, incandescent lamps, 230 V halogen lamps, low-voltage halogen lamps with conventional or electronic transformers, and dimmable energy-saving halogen lamps. For dimmable Retrofit-LEDs (LEDi). Dimming function is available also without prior programming (pre-configured). Configuration can be changed later via the web interface (groups, scenes, etc.). For contacting 1gang rocker 6230-10-xxx, 6231-10-xxx, 6232-10-xxx und 6234-10-xxx. 2-wire connection (neutral conductor not required) 3-wire connection technology is possible as an option for improved load behaviour (for details see the online operating manual). With 230 V extension unit input (dimming brighter/darker, switching). With fixing claws.

In	ıst	:al	la	ti	O	n

Instructions and No document needed

SDA-F-1.1.PB.1-WL 2/3

Mounting Type \_\_\_\_\_ Flush Mounted

Technical	
Data Sheet, Technical Information	No document needed
Number of Outputs	1
Compatible Bus Systems	free@home wireless
Product Range	free@home
Number of Batteries	0

Electrical	
Rated Voltage (U <sub>r</sub> )	230 V
Rated Operational Voltage	230230 V
Auxiliary Voltage AC/DC	230 V AC/DC
Rated Frequency (f)	50 / 60 Hz

Material Compliance	
RoHS Information	9AKK104295D8727
RoHS Status	Following EU Directive 2002/95/EC August 18, 2005 and amendment
REACH Declaration	2CKA309999E9999
REACH Information	False - does not contains substances > 0.1 mass percentage
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Environmental	
Ambient Air	Operation -5 +45 °C
Temperature	
Degree of Protection	IP20

Dimensions	
Product Net Width	45 mm
Product Net Height	45 mm
Product Net Depth / Length	40 mm
Product Net Weight	61 g
Built-In Depth (t <sub>2</sub> )	32 mm

Certificates and Declarations	
Declaration of Conformity - CE	2CKA100000E3573
Declaration of Conformity - UKCA	2CKA400000E0315

SDA-F-1.1.PB.1-WL 3/3

Classifications	
ETIM 9	EC001094 - Dimming actuator for bus system
eClass	V11.0 : 27143123
UNSPSC	39121801
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer

## Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Building\ and\ Home\ Automation\ Solutions \rightarrow free@home \rightarrow Lighting\ Control \rightarrow Universal\ Dim\ Actuators$ 

