SBR/U6.0.1-84 1/3



PRODUCT-DETAILS

SBR/U6.0.1-84 SBR/U6.0.1-84 HVAC-device,6f. CE



| General Information | |
|-----------------------|---|
| Extended Product Type | SBR/U6.0.1-84 |
| Product ID | 2CKA006330A0004 |
| EAN | 4011395255667 |
| Catalog Description | SBR/U6.0.1-84 HVAC-device,6f. CE |
| Long Description | Freely configurable multifunction control element. With integrated KNX bus coupler. With labelling field. Support of KNX functions through innovative colour concept (yellow=lighting, blue=blind, orange=RTC, magenta=scene and white=neutral/no function assigned) or standard illumination red/green. Push switch function: switching / dimming / blind / sending values / scenes etc. For activating heating, ventilation and fan coil actuators. Master/slave configuration. With base-load operation. The fan stage can be switched manually or in automatic mode. Class of temperature controller 1 Contribution to space heating energy efficiency 1.0%. Number of bus subscribers: 1 |

| Installation | |
|--------------------------|----------------------------------|
| Instructions and Manuals | 2CKA000073BB9649 |
| Mounting Type | Flush Mounted Surface Mounted |

Technical

SBR/U6.0.1-84 2/3

| No document needed |
|---|
| 6 |
| KNX (TP) |
| KNX |
| |
| |
| ABB Tenton® |
| Untreated Glossy |
| Thermoplastic |
| RAL 9016 - Traffic White |
| studio white |
| |
| 2CKA200000E7858 |
| Following EU Directive 2011/65/EU |
| 2CKA309999E9999 |
| True - contains substances > 0.1 mass percentage |
| 9AKK108468A3363 |
| Operation -5 +45 °(IP2 |
| |
| |
| 90.1 mg |
| |
| 117.1 mm |
| 117.1 mm 44.2 mm |
| 117.1 mm 44.2 mm 187 <u>c</u> |
| 117.1 mm 44.2 mm 187 g |
| 117.1 mm 44.2 mn 187 g 30.7 mm |
| 117.1 mm 44.2 mn 187 g 30.7 mm |
| 117.1 mm 44.2 mn 187 g 30.7 mm |
| 117.1 mm 44.2 mm 187 g 30.7 mm 2CKA100000E4072 |
| 117.1 mm 44.2 mm 187 g 30.7 mm 2CKA100000E4072 |
| 90.1 mm 117.1 mm 44.2 mm 187 g 30.7 mm 2CKA100000E4072 EC001101 - Room temperature controller for bus system V11.0 : 27143133 39121803 5. Small Equipment (No External Dimension More Than 50 cm) |
| |

SBR/U6.0.1-84 3/3

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Building\ and\ Home\ Automation\ Solutions \rightarrow KNX \rightarrow User\ Operation \rightarrow ABB-Tenton @ \rightarrow 6\ fold\ with\ Room\ Thermostat\ Co2$









3605