

PRODUCT-DETAILS

2CSK1307CH

Automatic RCD, 1P+N, C6 - 10 mA, breaking capacity 1.5kA 10 mA White - Chiara



General Information		
Product ID		2CSK1307CH
EAN		8012542006855
Catalog Description	Automatic RCD, 1P+N, C6 - 10 mA, breaking of	capacity 1.5kA 10 mA White - Chiara
Long Description	Automatic RCD, 1P+N,	C6 - 10 mA, breaking capacity 1.5kA
Installation		
Instructions and Manuals		2CSC600290D0201
Technical		
Data Sheet, Technical Information		2CSC600290D0201
Type of Residual Current		Type A
Rated Service Short- Circuit Breaking Capacity (I _{cs})		1.5 kA
Maximum Surge Current		3 kA
Number of Poles		1
@ 2024 APP All rights received	2024/04/12	Cubicat to abou

2CSK1307CH 2/3

Illumination	Non-illuminated
Rated Cross-Section	1 - Solid-Core 66 mm² 4 - Multi-Wired 66 mm²
Electrical	
Short-Circuit Current Rating (SCCR)	10 A
Rated Voltage (U _r)	230 V
Rated Operational Voltage	acc. to IEC 60898-1 230 V
Rated Insulation Voltage (U_i)	230 V
Rated Impulse Withstand Voltage ($U_{\rm imp}$)	4 kV
Input Voltage Type	AC
Rated Current (I _n)	6 A
Rated Residual Current	10 mA
Rated Frequency (f)	50 / 60 Hz
Design	
Design Range	Chiara
Surface Finishing	Basic
Material	Plastic
Color	White
Material Compliance Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363
Environmental	
Ambient Air Temperature	Operation -540 °C
Degree of Protection Pollution Degree	IP20 1
Dimensions	
Width in Number of Modular Spacings	2
Product Net Width	0 mm
Product Net Height Product Net Depth /	0 mm
Length Product Net Weight	0.01 kg
Built-In Depth (t ₂)	40 mm
Certificates and Declarations	
Declaration of Conformity - CE	No declaration needed
- OL	

Illumination

Non-illuminated

2CSK1307CH 3/3

Classifications	
ETIM 9	EC000003 - Residual current circuit breaker (RCCB)
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer

Categories

Low Voltage Products and Systems → Wiring Accessories - Light Switch Ranges → Cover Plates and Control Elements → Protection Devices

