2CSK1308CH 1/3



PRODUCT-DETAILS

## 2CSK1308CH

# Automatic RCD, 1P+N, C10 - 10 mA, breaking capacity 3kA 10 mA White - Chiara



2CSK1308CH
8012542006954
Automatic RCD, 1P+N, C10 - 10 mA, breaking capacity 3kA 10 mA White - Chiara
Automatic RCD, 1P+N, C10 - 10 mA, breaking capacity 3kA

Installation	
Instructions and	2CSC600290D0201
Manuals	

Technical	
Data Sheet, Technical Information	2CSC600290D0201
Type of Residual Current	Туре А
Rated Service Short- Circuit Breaking Capacity (I <sub>cs</sub> )	3 kA

2CSK1308CH 2/3

Maximum Surge Current	3 kA
Number of Poles	1
Illumination	Non-illuminated
Rated Cross-Section	1 - Solid-Core 66 mm² 4 - Multi-Wired 66 mm²
Electrical	
Short-Circuit Current Rating (SCCR)	10 A
Rated Voltage (U <sub>r</sub> )	230 V
Rated Operational Voltage	acc. to IEC 60898-1230 V
Rated Insulation Voltage (U <sub>i</sub> )	230 V
Rated Impulse Withstand Voltage (U <sub>imp</sub> )	4 kV
Input Voltage Type	AC
Rated Current (In)	6 A
Rated Residual Current	10 mA
Rated Frequency (f)	50 / 60 Hz
 Design	
Design Range	Chiara
Surface Finishing	Basic
Material	Plastic
Color	White
Material Compliance	
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363
Environmental	
Ambient Air Temperature	Operation -540 °C
Degree of Protection	IP20
Pollution Degree	1
Dimensions	
Width in Number of Modular Spacings	2
Product Net Width	0.06 m
Product Net Height	50 m
Product Net Depth / Length	55 m
Product Net Weight	0.01 kg

2CSK1308CH 3/3

#### **Certificates and Declarations**

Declaration of No declaration needed Conformity - CE

#### Classifications

ETIM 9	EC000003 - Residual current circuit breaker (RCCB)
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer

### **Categories**

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Wiring\ Accessories\ -\ Light\ Switch\ Ranges \rightarrow Cover\ Plates\ and\ Control\ Elements \rightarrow Protection\ Devices$ 









3605