



PRODUCT-DETAILS

LT/U 1.1.CH

2CSKK5000C LT/U 1.1.CH - Transponder reader, Chiara



General Information	
Extended Product Type	LT/U 1.1.CH
Product ID	2CSKK5000C
EAN	8012542263753
Catalog Description	2CSKK5000C LT/U 1.1.CH - Transponder reader, Chiara
Long Description	The device is equipped with two bistable relays (8 A, 250 Vac), and three voltage-free, non-optically insulated inputs; the 5-Vdc scanning voltage is generated by the device itself. The transponder reader has on the front four LEDs for signaling indications. It requires a 10...32Vdc/12...24Vac auxiliary power supply to ensure its operation even in case of KNX voltage failure.

Installation	
Instructions and Manuals	2CSN600045D0201
Mounting Type	Flush Mounted

Technical	
-----------	--

Data Sheet, Technical Information	2CSN600050D0901
Suitable For	2-wire
Product Range	KNX
Number of Batteries	0

Electrical

Power Supply Type	Bus System
-------------------	------------

Design

Surface Finishing	Glossy
Material	Plastic
RAL Number	RAL 9003 - Signal White
Color	White

Material Compliance

Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363
---	-----------------

Environmental

Degree of Protection	IP20
----------------------	------

Dimensions

Product Net Width	66 mm
Product Net Height	46 mm
Product Net Depth / Length	44 mm
Product Net Weight	0.1 kg

Certificates and Declarations

Declaration of Conformity - CE	2CSC600002U5101
--------------------------------	-----------------

Classifications

ETIM 9	EC002971 - System device clinic-installation
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer

Categories

Low Voltage Products and Systems → Building and Home Automation Solutions → KNX → User Operation → Chiara → Transponder Readers and Card Holders

