TR/U 1.1.ZS 1/3



PRODUCT-DETAILS

## TR/U 1.1.ZS

## TR/U 1.1.ZS Card Reader Zenit Silver



Genera	ı	nfor	ma	tion
uenera	ı	ntor	ma	บดาเ

 Extended Product Type
 TR/U 1.1.ZS

 Product ID
 2CSY242210R5000

 EAN
 8012542356837

Catalog Description

TR/U 1.1.ZS Card Reader Zenit Silver

operation even with bus voltage failure.

The "transponder reader" is a flush-mounting device for British Standard wall boxes, designed to realize access control systems with a communication support based on KNX bus. It is equipped with one relay (4A @24 V AC/DC) and one input to be used for connecting external conventional card-holder (e.g. Zenit wiring accessories card-holder). The output can be programmed in three different ways: "Linked to access control", receiving in this case switching commands from the device itself (according to transponder card validation); being a standard KNX Switch actuator output, able to be controlled by every KNX standard devices; "linked to card-holder", that means that the relay is switched according to closing/opening internal input contact available on transponder reader. The bicolor (red-green) LED placed on the front of the device allow you to monitor device operation and can be also switched ON/OFF in the proper color according to KNX telegram (for example for DND/MUR purposes). The transponder reader can be configured with ABB Access control software in order to behave as transponder programming device. The transponder reader requires a 12...24 V AC/DC external power supply to ensure its

Long Description

Installation

Instructions and Manuals 2CKA001473B5155

TR/U 1.1.ZS 2/3

Technical	
Data Sheet, Technical	2CKA000173B5036
Information Product Range	KNX
r roddet Hange	MVA
Electrical	
Power Supply Type	Integrated
Design	
Color	Silver
Material Compliance	
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363
Dimensions	
Product Net Width	44 mm
Product Net Height	43 mm
Product Net Depth / Length	44 mm
Product Net Weight	0.050 kg
Certificates and Declarations	
Declaration of Conformity - CE	2CSC500009D2701
Classifications	
ETIM 9	EC002971 - System device clinic-installation
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer

TR/U 1.1.ZS 3/3

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Building\ and\ Home\ Automation\ Solutions \rightarrow KNX \rightarrow User\ Operation \rightarrow Zenit\ /\ Olas \rightarrow Transponder\ Readers\ and\ Card\ Holders$ 





