TR/U 1.1.ZC 1/3



PRODUCT-DETAILS

TR/U 1.1.ZC

TR/U 1.1.ZC Card Reader Zenit Champagne



General Information	
Extended Product Type	TR/U1.1.ZC
Product ID	2CSY247300R5000
EAN	8012542356837
Catalog Description	TR/U 1.1.ZC Card Reader Zenit Champagne
Long Description	The "transponder reader" is a flush-mounting device for British Standard wall boxes, designed to realize access control systems with a communication support based on KNX bus. It is equipped with one relay (4A @24 V AC/DC) and one input to be used for connecting external conventional card-holder (e.g. Zenit wiring accessories card-holder). The output can be programmed in three different ways: "Linked to access control", receiving in this case switching commands from the device itself (according to transponder card validation); being a standard KNX Switch actuator output, able to be controlled by every KNX standard devices; "linked to card-holder", that means that the relay is switched according to closing/opening internal input contact available on transponder reader. The bicolor (red-green) LED placed on the front of the device allow you to monitor device operation and can be also switched ON/OFF in the proper color according to KNX telegram (for example for DND/MUR purposes). The transponder reader can be configured with ABB Access control software in order to behave as transponder programming device. The transponder reader requires a 1224 V AC/DC external power supply to ensure its operation even with bus voltage failure.

TR/U 1.1.ZC 2/3

Installation	
Instructions and Manuals	2CKA001473B515
Technical	
Data Sheet, Technical Information	2CKA000173B503
Product Range	KN
 Electrical	
Power Supply Type	Integrated
Design	
Color	Champagne
Material Compliance	
Conflict Minerals Reporting Template (CMRT)	9AKK108468A336
Dimensions	
Product Net Width	44 mn
Product Net Height	43 mm
Product Net Depth / Length	44 mn
Product Net Weight	0.050 kg
Built-In Depth (t ₂)	43 mn
Certificates and Declarations	
Declaration of Conformity - CE	2CSC500009D270
ETIM 9	EC002971 - System device clinic-installation
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm
WEEE Category	

TR/U 1.1.ZC 3/3

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Building\ and\ Home\ Automation\ Solutions \rightarrow KNX \rightarrow User\ Operation \rightarrow Zenit\ /\ Olas \rightarrow Transponder\ Readers\ and\ Card\ Holders$





