STD-W5.1A 1/3



PRODUCT-DETAILS

## STD-W5.1A Flood detector



General Information	
Extended Product Type	STD-W5.1A
Product ID	2CSY255191R0708
EAN	801254255191
Catalog Description	STD-W5.1A Flood detecto
Long Description	It detects the presence of water. The minimum detectable level of the liquid is 1 millimeter, but it can be adjusted to higher levels It is equipped with an anti-tamper (breakage or removal), self-diagnostics and control of battery charge device.  The detector ic composed by the interface module and the flood detection probe. It features a bidirectional communication with the central unit that supervises it with a programmable supervision interval (typically every 15 minutes).ilt is possible to configure this parameter during the system commissioning Spare lithium battery (Order code: 2CSY255331R0802)

Technical	
Operational Voltage	3 V
Continuous Operating Current $(I_c)$	1.4 A
Transmission Standard	Water
Mounting Type	Surface Mounted
Color	white

STD-W5.1A 2/3

Battery Chemical Composition	Lithium
Battery Type	Portable
Battery Weight	0.02 kg
Number of Batteries	1
Dimensions	
Product Net Width	190 mm
Product Net Height	121 mm
Product Net Depth / Length	70 mm
Product Net Weight	0.410 kg
Ordering	
Package Level 1 Units	box 1 piece
Package Level 1 Gross	0.44 kg
Weight	
Certificates and Declarations	
Declaration of Conformity	No declaration needed
- CE	
Installation	
Instructions and Manuals	2CSM600715D0901
	2CSM600715D0902
Popular Downloads	
Data Sheet, Technical	No document needed
Information	
Classifications	
ETIM 8	EC001764 - Technical detector for intrusion detection system
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	<u>85311030</u>

STD-W5.1A 3/3

## Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Building\ and\ Home\ Automation\ Solutions \rightarrow Intrusion\ Alarm\ Systems \rightarrow Alarm\ Systems - secure@home \rightarrow Technical\ Detectors\ (Wireless\ 868Mhz)$ 









3605