

PRODUCT-DETAILS

## Sentry USR22 Sentry USR22 Safety relay



General Information	
Extended Product Type	Sentry USR22
Product ID	2TLA010070R0400
EAN	7350024483383
Catalog Description	Sentry USR22 Safety relay
Long Description	Sentry USR22 Universal safety relay with relay outputs 2NO+2 delayable NO, +24VDC power supply and screw terminals. For monitoring of safety devices with contacts, 1 or 2 equivalent or antivalent channels, safety devices with OSSD outputs, two-hand devices, safety mats and safety edges/bumpers. Timer function 0-999 seconds with a better accuracy than 1%: OFF-delay, ON-delay, Time bypass and Time reset. A display on front facilitates configuration and troubleshooting by displaying error codes and error log. A custom configuration can be protected by password. Manual or automatic reset selectable. Sentry safety relays cover various types of safety applications up to PLe / SIL3. Basic models provide reliable supervision of simpler safety functions, while universal models provide advanced features and high flexibility. Models with display offer preset configurations and extensive information to further simplify troubleshooting. Additional variants offer a high accuracy timer function of ± 1% and an adjustable time setting range from 0-999 s. High output current capacity of up to 6 A can save the use of an intermediary contactor.

 $\ensuremath{\textcircled{}}$  2024 ABB. All rights reserved.

Ordering	
Minimum Order Quantity	1 piece
Customs Tariff Number	85364900
Product Main Type	USR
Product Name	Safety relay
Function	Safety relay for monitoring of safety devices
Sub-Function	Start/test input, configurable Manual/Auto reset and Timer, Display (error indication and error log)
Special Functions	Configurable (manual/auto reset, type of input, timer type, time) with display (error indication and error log)
Popular Downloads	211 0010027/ 0201
Data Sheet, Technical Information	2TLC010037L0201
Instructions and Manuals	2TLC010073M0201
Dimension Diagram	2TLC010001U0201
Wiring Diagram	2TLC010017T0001
CAD Dimensional Drawing	2CDC001079B0201
Marketing Video	2TLC010019N0201 2TLC010018N0201
Dimensions	
Product Net Depth / Length	120 mm
Product Net Height	120 mm
Product Net Width	22.5 mm
Product Net Weight	0.229 kg
Safety Information	
Certification Agency	cULus
	TÜV SÜD CE
	CCC
	RCM S
	UKCA
	KC
Performance Level (PL) Safety Integrity Level (SIL)	Up to e 3
Technical	
Number of Outputs	Failsafe, Delayed Contacts 2 Failsafe (Relay) 2
Rated Control Supply Voltage (U <sub>s</sub> )	24 V DC
Time Range	0 999 seconds
Environmontal	
Environmental Ambient Air Temperature	Operation -25 +65 °C
Degree of Protection	Storage -40 +70 °C IP20
© 2024 ABB. All rights reserved.	2024/04/12 Subject to change

nge without notice

10% ... 90%; no icing; occasional condensation

Material Compliance	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	2CMT2022-006480
RoHS Information	2CMT2022-006499
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA	2CMT2023-006522
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Certificates and Declarations	
CQC Certificate	CQC2017010303977544
cUL Certificate	2TLC010006D0201
cULus Certificate	2TLC010007D0201
Declaration of Conformity - CCC	2020980303000244
Declaration of Conformity - CE	2TLC010010D0201
Declaration of Conformity - UKCA	2TLC010190D0201
KC Certificate	2TLC010048D0201
TÜV Certificate	2TLC010008D0201

Container Information	
Package Level 1 Units	box 1 piece
Package Level 1 Width	125 mm
Package Level 1 Depth / Length	31 mm
Package Level 1 Height	129 mm
Package Level 1 Gross Weight	0.29 kg
Package Level 1 EAN	7350024483383

Classifications	
eClass	V11.0 : 27371819
ETIM 7	EC001449 - Device for monitoring of safety-related circuits
ETIM 8	EC001449 - Device for monitoring of safety-related circuits
ETIM 9	EC001449 - Device for monitoring of safety-related circuits
IDEA Granular Category Code (IGCC)	5367 >> Control relay
UNSPSC	39122331
Object Classification Code	К
E-Number (Finland)	2712532
E-Number (Sweden)	3860829

## Accessories

## Sentry USR22

Identifier	Description	Туре	Quantity	Unit Of Measure
2TLA010099R0000	Sentry S30A Terminal block	Sentry S30A	1	piece
2TLA010099R0100	Sentry S30B Coding kit	Sentry S30B	1	piece
2TLA010099R0001	Sentry S30C Terminal block	Sentry S30C	1	piece

## Categories

Low Voltage Products and Systems $ ightarrow$ Control Products $ ightarrow$ Electronic Relays and Controls $ ightarrow$ Safety Relays $ ightarrow$ Safety Timers
$\label{eq:low-low-control} \text{Low-Voltage-Products} \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \$
Low Voltage Products and Systems $\rightarrow$ Control Products $\rightarrow$ Safety Products $\rightarrow$ Safety Relays $\rightarrow$ Safety Timers
Low Voltage Products and Systems $ ightarrow$ Control Products $ ightarrow$ Safety Products $ ightarrow$ Safety Relays $ ightarrow$ Universal Safety Relays

