

PRODUCT-DETAILS

## JSHD4H2A 0.15m JSHD4H2A 0.15m Three-position dual pushbutton



Extended Product Type	JSHD4H2A 0.15m
Product ID	2TLA020002R0200
EAN	7350024454833
Catalog Description	JSHD4H2A 0.15m Three-position dual pushbutton
	JSHD4H2A 0.15m is a three-position device for external panel mounting with 6 leads, each 150mm long, and mounting holes up left.
Long Description	Three-position devices are used to allow a limited movement of the machine when the operator is in the dangerous area, for example during troubleshooting, test running and programming.

Ordering	
Minimum Order Quantity	1 piece
Customs Tariff Number	85369095
Product Main Type	JSHD4H2
Product Name	Three-position dual pushbutton
Function	Three-position dual pushbutton usual mounted on another device, e.g. a robot pendant
Status Indicator	No

Popular Downloads	
Data Sheet, Technical	2TLC010126L0201
Information	000000000000000000000000000000000000000
CAD Dimensional Drawing	2CDC001079B020
Marketing Video	2TLC010018N020
Dimensions	
Product Net Depth / Length	52 mr
Product Net Height	56 mr
Product Net Width	106 mm
Product Net Weight	0.154 kc
Safety Information	
Certification Agency	CE
	cURus Kiwa
Performance Level (PL)	Up to e
Technical	
	Contract
Communication Interface Connection Configuration	Contacts 6 leads, 150 mm each
Number of Contacts CO	
Number of Contacts NC	
Number of Contacts NO	(
Rated Operational Current DC-12 (I <sub>e</sub> )	(24 V) 0.02 A
Environmental	
Ambient Air Temperature	Operation 0 +50 °C Storage -20 80 °C
Degree of Protection	IP65
Material	Housing: PP (polypropylene with mineral filling Rubber: Thermoplastic elastomer on PP basis Steering T: PP with fiberglass filling
Material Compliance	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	2CMT2022-006480
RoHS Information	2CMT2022-006499
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA	2CMT2023-006522
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm
Contification and Declarations	
Certificates and Declarations	Ne posification and a
CQC Certificate	No certification needed

© 2024 ABB. All rights reserved.

Subject to change without notice

cULus Certificate	2TLC010153D0201
cURus Certificate	2TLC010153D0201
Declaration of Conformity - CCC	No declaration needed
Declaration of Conformity - CE	2TLC172022D0201
Declaration of Conformity - UKCA	2TLC010152D0201
SEMKO Certificate	2TLC172032D0201
UR Certificate	2TLC010153D0201

Container Information	
Package Level 1 Units	bag 1 piece
Package Level 1 Width	174 mm
Package Level 1 Depth / Length	268 mm
Package Level 1 Height	57 mm
Package Level 1 Gross Weight	0.156 kg
Package Level 1 EAN	7350024454833

Classifications	
eClass	V11.0 : 27371238
ETIM 7	EC002571 - Agreement switch
ETIM 8	EC002571 - Agreement switch
ETIM 9	EC002571 - Agreement switch
IDEA Granular Category Code (IGCC)	5219 >> Switch part or accessory
UNSPSC	39122221
Object Classification Code	В

## Categories

 $\text{Low Voltage Products and Systems} \rightarrow \text{Control Products} \rightarrow \text{Safety Products} \rightarrow \text{Safety Control Devices} \rightarrow \text{JSHD}$ 

