



PRODUCT-DETAILS

JSTD25H

JSTD25H Two-Hand device



General Information	
Extended Product Type	JSTD25H
Product ID	2TLA020007R6300
EAN	7350024460346
Catalog Description	JSTD25H Two-Hand device
Long Description	JSTD25H is a two-hand device with two JSTD1-B Safeball. The Safeball are mounted on each end of a 44x88 aluminum profile designed for two-hand applications. The Safeball are pre-wired to a M12-8 male connector and protected by flanges. The JSTD25 control stations are pre-built two-hand devices offering the good ergonomics of Safeball. They can be used as fixed devices that are easy to install, or as mobile devices. All models are equipped with flanges to protect the Safeball from accidental operation, and from damage if the device is dropped on the floor when used as mobile device.

Ordering	
Minimum Order Quantity	1 piece
Customs Tariff Number	85365011
Product Main Type	JSTD25
Product Name	Two-Hand device

Popular Downloads

Data Sheet, Technical Information	2TLC010001C0202
Data Sheet, Technical Information (Part 2)	2TLC010069D0201
Instructions and Manuals	2TLC172185M0201
CAD Dimensional Drawing	2CDC001079B0201
Marketing Video	2TLC010018N0201

Dimensions

Product Net Depth / Length	90.5 mm
Product Net Height	130 mm
Product Net Width	370 mm
Product Net Weight	1.167 kg

Safety Information

Performance Level (PL)	Up to e
------------------------	---------

Technical

Connection Configuration	M12-8 male
--------------------------	------------

Environmental

Degree of Protection	IP65
----------------------	------

Material Compliance

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	2CMT2022-006480
RoHS Information	2CMT2022-006499
SCIP	e6eafce3-c57e-4ce2-bac1-d4a848a81068 Sweden (SE)
Simplified SCIP	bc535453-2c62-434a-936d-632eb3018910 Germany (DE) 1419311f-cd02-43d5-a09b-6167503ca448 Belgium (BE) c6f16d50-f4b7-432c-b4f5-d6789e49adf6 Poland (PL) d12f15b1-a565-420a-811f-f944c9fa745b Norway (NO) 819d43dd-8284-4294-b4c7-a18873b3e282 Finland (FI) dc76a488-0456-44c5-b579-3aaf68f71907 Belgium (BE) b3bddf6b-0da7-4ae4-ad76-466fbcd636b Italy (IT) 0c883e7e-33d1-4abf-8fa8-4ed7afdada7 Greece (GR) b6f8afc1-7623-4328-b474-0d87599e844b Portugal (PT) 3ef99568-9507-456c-97a3-afb7e30079c9 Bulgaria (BG) 74ae2798-9683-41d0-a9bc-99f4aaed9492 Sweden (SE) 5d262e0d-78df-419d-a458-f90b7ee2e4c4 Poland (PL) e772bc7b-0203-47cd-ad19-61cbf4c867a0 France (FR) 38d47533-afea-4d00-9981-6eb8bf979af9 Germany (DE)

	d9e1cd5b-9bc3-4717-8cd4-18c8d880aa0e Germany (DE)
	c2d8ae49-7182-4c5b-870b-89792e0a68f2 France (FR)
	fff31e70-285b-4686-8d54-06f04f17b26b Hungary (HU)
	cff9ec80-e98f-4464-af21-6c6496e89d4b Spain (ES)
	f4ab0a33-f7aa-425b-80ac-2eb281fdc271 Czech Republic (CZ)
	62148f39-d723-4ff7-b989-2532e096747b Poland (PL)
	c5cd9d81-9c81-4fb9-8857-c96886b0a336 Netherlands (NL)
	4b5763d5-2db3-40c1-b538-7634ebff4990 Hungary (HU)
	77be154d-1898-45c7-afe3-56ddc0f2dc02 Estonia (EE)
	5b2d5749-854c-4b28-ab17-d99adb568dba Germany (DE)
	bf936f62-5de1-4e1f-b877-7ed74a24b683 Denmark (DK)
	21bc1148-308c-4c54-b4b8-b262bcf593db Germany (DE)
	8d5b1ac0-e414-4275-b6ac-5bdc36c3193c Croatia (HR)
Toxic Substances Control Act - TSCA	2CMT2023-006522
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Certificates and Declarations

Declaration of Conformity - CCC	No declaration needed
Declaration of Conformity - CE	2TLC172023D0201
Declaration of Conformity - UKCA	2TLC010204D0201
SEMKO Certificate	2TLC172034D0201

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	38.2 mm
Package Level 1 Depth / Length	95 mm
Package Level 1 Height	140 mm
Package Level 1 Gross Weight	1.317 kg
Package Level 1 EAN	7350024460346

Classifications

eClass	V11.0 : 27371219
ETIM 7	EC001260 - Two-hand control device
ETIM 8	EC001260 - Two-hand control device
ETIM 9	EC001260 - Two-hand control device
IDEA Granular Category Code (IGCC)	3584 >> Safety Control Module
UNSPSC	32151802
Object Classification Code	B

Categories

Low Voltage Products and Systems → Control Products → Safety Products → Safety Control Devices → JSTD25

