Adam C DYN-Info M12-5



1/4

PRODUCT-DETAILS

Adam C DYN-Info M12-5 Adam C DYN-Info M12-5 Sensor



General Information	
Extended Product Type	Adam C DYN-Info M12-5
Product ID	2TLA020051R5101
EAN	7350024486599
Catalog Description	Adam C DYN-Info M12-5 Sensor
Long Description	Adam safety sensor with DYNlink signal and information output. Used with an Eva actuator to form a non-contact safety sensor Eden. M12-5 male connector. 4 pcs of DA 1B distance plates and 4 pcs of DA 2B distance rings are included. Coated PCBA for extra protection in demanding environments.

Ordering	
Minimum Order Quantity	1 piece
Customs Tariff Number	8536508090
Product Main Type	Eden
Product Name	Sensor
Function	Non-contact safety sensor used as interlocking device - Actuator to be ordered separately
Sub-Function	Info signal
Status Indicator	Yes

Adam C DYN-Info M12-5

Popular Downloads	
Data Sheet, Technical Information	2TLC010044L0201
Data Sheet, Technical Information (Part 2)	2TLC172209D0201
Instructions and Manuals	2TLC172271M0201
Marketing Video	2TLC010019N0201 2TLC010018N0201
Dimensions	
Product Net Depth / Length	12 mm
Product Net Height	75.2 mm
Product Net Width	30 mm
Product Net Weight	0.026 kg
Safety Information	
Certification Agency	cCSAus
Safety Category	4
Performance Level (PL)	Up to e
Safety Integrity Level (SIL)	3
Technical Communication	DYNlink
Interface Connection	M12-5 male
Configuration	
Number of Outputs	Non-Failsafe, Undelayed Contacts 0 Non-Failsafe, Undelayed Semiconductors 1
Operating Distance (S _n)	15 mm
PCB Coated Probability of Dangerous	Yes 4.5 10 ⁻⁹ hour
Failure per Hour (PFDH) Rated Control Supply Voltage (U _S)	24 V DC
Tarketalin (CC)	
Technical UL/CSA	
Technical UL/CSA Enclosure Type UL/CSA	4X
	4X
Environmental Ambient Air	Operation -40 70 °C
Enclosure Type UL/CSA Environmental	Operation -40 70 °C Storage -40 +70 °C IP67
Environmental Ambient Air Temperature	Operation -40 70 °C Storage -40 +70 °C IP67 IP69K Housing: Plastic (PBT)

Material Compliance		
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658	
REACH Declaration	2CMT2022-006480	
RoHS Information	2CMT2022-006499	
Toxic Substances Control Act - TSCA	2CMT2023-006522	
WEEE B2C / B2B	Business To Business	
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)	

Certificates and Declarations	
CQC Certificate	No declaration needed
cULus Certificate	2TLC172139D0201
Declaration of Conformity - CCC	No declaration needed
Declaration of Conformity - CE	2TLC172133D0201
Declaration of Conformity - UKCA	2TLC010159D0201
TÜV Certificate	2TLC172134D0201
UL Certificate	2TLC172139D0201

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Width	0.016 m
Package Level 1 Depth / Length	0.075 m
Package Level 1 Height	0.075 m
Package Level 1 Gross Weight	0.052 kg
Package Level 1 EAN	7350024486599

Classifications		
eClass	V11.0 : 27272402	
ETIM 7	EC002544 - Magnetic proximity switch	
ETIM 8	EC002544 - Magnetic proximity switch	
ETIM 9	EC002544 - Magnetic proximity switch	
UNSPSC	39122221	
Object Classification Code	В	
E-Number (Sweden)	3834855	

Adam C DYN-Info M12-5 4/4

Categories

 $Low\ Voltage\ Products \rightarrow Safety\ Products \rightarrow Safety\ Sensors,\ Switches\ and\ Locks \rightarrow Eden$





