

PRODUCT-DETAILS

Adam C OSSD-Info M12-8 Adam C OSSD-Info M12-8 Sensor



General Information	
Extended Product Type	Adam C OSSD-Info M12-8
Product ID	2TLA020051R5701
EAN	7350024486636
Catalog Description	Adam C OSSD-Info M12-8 Sensor
Long Description	Adam safety sensor unit with OSSD signals and information output. M12-8 male connector, IP69K, yellow. 4pcs of DA 1B distance plates and 4pcs of DA 2B distance rings are included. Coated PCBA for extra protection in harsh environments.

Ordering	
Minimum Order Quantity	1 piece
Customs Tariff Number	8536508090
Product Main Type	Eden
Product Name	Sensor
Function	Non-contact safety sensor used as interlocking device - Actuator to be ordered separately
Sub-Function	Info signal
Status Indicator	Yes

Adam C OSSD-Info M12-8

Data Sheet, Technical	
Information	2TLC010044L0201
Data Sheet, Technical Information (Part 2)	2TLC172213D0201
Instructions and Manuals	2TLC172272M0201
Marketing Video	2TLC010019N0201 2TLC010018N0201
Dimensions	
Product Net Depth / Length	12 mm
Product Net Height	75.2 mm
Product Net Width	30 mm
Product Net Weight	0.026 kg
Safety Information	
Certification Agency	cCSAus
Safety Category	4
Performance Level (PL)	Up to e
Safety Integrity Level (SIL)	3
Technical Communication Interface	OSSD
Connection Configuration	M12-8 male
Number of Outputs	Non-Failsafe, Undelayed Contacts 0
Number of Outputs	Non-Failsafe, Undelayed Semiconductors 1
·	-
Operating Distance (S _n) PCB Coated	15 mm Yes
Operating Distance (Sn) PCB Coated Probability of Dangerous Failure per Hour (PFDH)	15 mm Yes
Operating Distance (S _n) PCB Coated Probability of Dangerous	15 mm Yes 4.5 10 ⁻⁹ hour
Operating Distance (S _n) PCB Coated Probability of Dangerous Failure per Hour (PFDH) Rated Control Supply	15 mm Yes 4.5 10 ⁻⁹ hour
Operating Distance (S _n) PCB Coated Probability of Dangerous Failure per Hour (PFDH) Rated Control Supply Voltage (U _S)	15 mn Ye 4.5 10 ⁻⁹ hou
Operating Distance (S _n) PCB Coated Probability of Dangerous Failure per Hour (PFDH) Rated Control Supply Voltage (U _S)	15 mm Yes 4.5 10 ⁻⁹ hou 24 V DO
Operating Distance (S _n) PCB Coated Probability of Dangerous Failure per Hour (PFDH) Rated Control Supply Voltage (U _S) Technical UL/CSA	15 mm Yes 4.5 10 ⁻⁹ hour 24 V DC
Operating Distance (S _n) PCB Coated Probability of Dangerous Failure per Hour (PFDH) Rated Control Supply Voltage (U _S) Technical UL/CSA Enclosure Type UL/CSA Environmental Ambient Air	15 mm Yes 4.5 10 ⁻⁹ hour 24 V DC
Operating Distance (S _n) PCB Coated Probability of Dangerous Failure per Hour (PFDH) Rated Control Supply Voltage (U _s) Technical UL/CSA Enclosure Type UL/CSA	Non-Failsafe, Undelayed Semiconductors 1 15 mm Yes 4.5 10 ⁻⁹ hour 24 V DC 4X Operation -40 70 °C Storage -40 +70 °C IP67 IP69K
Operating Distance (S _n) PCB Coated Probability of Dangerous Failure per Hour (PFDH) Rated Control Supply Voltage (U _s) Technical UL/CSA Enclosure Type UL/CSA Environmental Ambient Air Temperature	15 mm Yes 4.5 10 ⁻⁹ hour 24 V DC 4X Operation -40 70 °C Storage -40 +70 °C IP67

Moulding: Epoxy 35 to 95%

Material Compliance		
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658	
REACH Declaration	2CMT2022-006480	
RoHS Information	2CMT2022-006499	
Toxic Substances Control Act - TSCA	2CMT2023-006522	
WEEE B2C / B2B	Business To Business	
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)	

Certificates and Declarations		
CQC Certificate	No declaration needed	
cULus Certificate	2TLC172264D0201	
Declaration of Conformity - CCC	No declaration needed	
Declaration of Conformity - CE	2TLC172261D0201	
Declaration of Conformity - UKCA	2TLC010160D0201	
TÜV Certificate	2TLC172297D0201	
UL Certificate	2TLC172264D0201	

Container Information		
Package Level 1 Units	1 piece	
Package Level 1 Width	0.016 m	
Package Level 1 Depth / Length	0.075 m	
Package Level 1 Height	0.075 m	
Package Level 1 Gross Weight	0.052 kg	
Package Level 1 EAN	7350024486636	

Classifications		
eClass	V11.0 : 27272402	
ETIM 7	EC002544 - Magnetic proximity switch	
ETIM 8	EC002544 - Magnetic proximity switch	
ETIM 9	EC002544 - Magnetic proximity switch	
UNSPSC	39122221	
Object Classification Code	В	
E-Number (Sweden)	3834861	

Adam C OSSD-Info M12-8

Categories

 $Low\ Voltage\ Products\ \rightarrow\ Safety\ Products\ \rightarrow\ Safety\ Sensors,\ Switches\ and\ Locks\ \rightarrow\ Eden$







4/4