Pluto D20 1/3



PRODUCT-DETAILS

Pluto D20 Pluto D20 Programmable safety controller



General Information	
Extended Product Type	Pluto D20
Product ID	2TLA020070R6400
EAN	7320500410578
Catalog Description	Pluto D20 Programmable safety controller
Long Description	Pluto is a cost effective, powerful and compact safety PLC for all machine safety applications. Most safety devices on the market can be connected directly to Pluto and multiple safety sensors can be connected to a single input and still achieve the highest safety level. Programming is done easily in the accompanying software Pluto Manager.
	Safety PLC with Pluto safety bus and analogue inputs. Totally 20 I/O: 4 combined failsafe analogue and digital inputs + 4 failsafe inputs + 8 non-failsafe outputs/failsafe inputs + 2 individually failsafe relay outputs + 2 individually failsafe transistor outputs.

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	8536411090
Product Main Type	Pluto
Product Name	Programmable safety controller

Analogue input range 0-10V/4-20mA.

Pluto D20 2/3

Popular Downloads		
Data Sheet, Technical Information		2TLC010035L0201
Data Sheet, Technical Information (Part 2)		2TLC172226D020
Instructions and Manuals		2TLC172001M0210
CAD Dimensional Drawing		2CDC001079B020
Marketing Video		2TLC010032N020 2TLC010018N020
Dimensions		
Product Net Depth / Length		120 mr
Product Net Height		84 mr
Product Net Width		45 mn
Product Net Weight		0.39 kc
Safety Information		
Performance Level (PL)		Up to e
Safety Integrity Level (SIL)		
		<u> </u>
Technical		
Diagnostic Coverage		Hig
Number of Inputs		Analog (0 10 V / 4 20 mA) 4 Failsafe 1
Number of Outputs		Failsafe (Transistor) 2 Failsafe (Relay) 2 Non-Failsafe 8
Protocol Type	MODBUS	S ASCII, Pluto Safety Bus, StatusBu
Rated Control Supply Voltage (U _s)		24 V D0
Supply Voltage		24 V D0
Matarial Committee and		
Material Compliance		0.11(1/100.107.1505
Conflict Minerals Reporting Template (CMRT)		9AKK108467A565
REACH Declaration		2CMT2022-00648
RoHS Information		2CMT2022-00649
RoHS Status	Following EU Directive 2011/65/EU and	Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA		2CMT2023-00652
WEEE B2C / B2B		Business To Busines
WEEE Category	5. Small Equipment (No E	xternal Dimension More Than 50 cm
Certificates and Declarations		
		No dealeration reads
CQC Certificate Declaration of Conformity - CCC		No declaration neede No declaration neede
Declaration of Conformity		2TLC172011D0202
© 2024 ARR All rights reserved	2024/04/12	Subject to char

Pluto D20 3/3

- CE

Declaration of Conformity - UKCA	2TLC010187D0201
TÜV Certificate	2TLC172005D0201

Container Information	
Package Level 1 Units	box 1 piece
Package Level 1 Width	90 mm
Package Level 1 Depth / Length	130 mm
Package Level 1 Height	57 mm
Package Level 1 Gross Weight	0.42 kg
Package Level 1 EAN	7320500410578

Classifications	
eClass	V11.0 : 27242207
ETIM 7	EC000236 - PLC CPU-module
ETIM 8	EC000236 - PLC CPU-module
ETIM 9	EC000236 - PLC CPU-module
IDEA Granular Category Code (IGCC)	3561 >> Programmable Logic Controller Module
UNSPSC	32151705
Object Classification Code	K
E-Number (Finland)	2712236
E-Number (Sweden)	3860080

Categories

 $Low\ Voltage\ Products\ \rightarrow\ Control\ Products\ \rightarrow\ Safety\ Products\ \rightarrow\ Programmable\ Safety\ Controllers\ \rightarrow\ Pluto\ Products\ \rightarrow\ Products\ Produc$

