Magne 4 DYN-Info



PRODUCT-DETAILS

Magne 4 DYN-InfoMagne 4 DYN-Info Lock



General Information	
Extended Product Type	Magne 4 DYN-Info
Product ID	2TLA042022R3400
EAN	7350024480993
Catalog Description	Magne 4 DYN-Info Lock
Long Description	Magne 4 DYN-Info is an electromagnetic lock providing safe interlocking thanks to an integrated ADAM DYN-Info safety sensor. Its M12-8 connector facilitates connexion. A +24VDC voltage is used for the locking. The holding force is up to 1500N and the protection class IP67. A combined "Locked and Closed" information output is available
	The Eva actuactor and the anchor plate must be ordered separately Magne is an electromagnetic process lock intended for locking doors and hatches. It is usually used to prevent unwanted process interruptions, e.g. during a welding operation. With Adam and Eva, a PLe can be reached for the interlocking function

Ordering	
Minimum Order Quantity	1 piece
Customs Tariff Number	8505902999
Product Main Type	Magne
Product Name	Lock

Electromagnetic process lock - Anchor plate and Eva actuator to be ordered separately

Data Shoot Tochnical	
Data Sheet, Technical Information	2TLC010045L020:
Instructions and Manuals	2TLC172315M0201
CAD Dimensional Drawing	2CDC001079B0201
Marketing Video	2TLC010018N0201
Dimensions	
Product Net Depth / Length	30 mm
Product Net Height	274 mm
Product Net Width	35 mm
Product Net Weight	0.7 kg
Safety Information	
Certification Agency	CE TÜV Süc cULus
Safety Category	
Performance Level (PL)	Up to a
Safety Integrity Level (SIL)	9
Technical	
Communication Interface	DYNlink
Connection Configuration	M12-8 male
Configuration Rated Control Supply Voltage (U $_{\mbox{\scriptsize s}}$)	
Configuration Rated Control Supply Voltage (Us) Environmental Ambient Air	24 V DC
Configuration Rated Control Supply Voltage (Us) Environmental Ambient Air Temperature	M12-8 male 24 V DC 24 V DC Operation -20 +50 °C
Configuration Rated Control Supply	Operation -20 +50 °C IP67 Housing: Anodized alunimum with some polycarbonate
Configuration Rated Control Supply Voltage (Us) Environmental Ambient Air Temperature Degree of Protection	24 V DC Operation -20 +50 °C
Configuration Rated Control Supply Voltage (Us) Environmental Ambient Air Temperature Degree of Protection Material Material Compliance Conflict Minerals Reporting Template	Operation -20 +50 °C IP67 Housing: Anodized alunimum with some polycarbonate
Configuration Rated Control Supply Voltage (Us) Environmental Ambient Air Temperature Degree of Protection Material Material Compliance Conflict Minerals	Operation -20 +50 °C IP6 Housing: Anodized alunimum with some polycarbonate Electromagnet: Iron with zinc-nickel coating

© 2024 ABB. All rights reserved.

Magne 4 DYN-Info

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA	2CMT2023-006522
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Certificates and Declarations	
CQC Certificate	No declaration needed
cUL Certificate	2TLC010012D0201
Declaration of Conformity - CCC	No declaration needed
Declaration of Conformity - CE	2TLC172262D0201
Declaration of Conformity - UKCA	2TLC010171D0201
TÜV Certificate	2TLC010013D0201

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Width	26 mm
Package Level 1 Depth / Length	290 mm
Package Level 1 Height	730 mm
Package Level 1 Gross Weight	1.075 kg
Package Level 1 EAN	7350024480993

Classifications	
eClass	V11.0 : 27144124
ETIM 7	EC001769 - Permanent magnet for door locking mechanism
ETIM 8	EC001769 - Permanent magnet for door locking mechanism
ETIM 9	EC001769 - Holding magnet for door locking system
IDEA Granular Category Code (IGCC)	7346 >> Lock sets
UNSPSC	46171503
Object Classification Code	В
E-Number (Sweden)	3831460

Magne 4 DYN-Info 4/4

Categories

 $Low\ Voltage\ Products\ \rightarrow\ Safety\ Products\ Products\ \rightarrow\ Safety\ Products\ \rightarrow\ Safety\ Products\ \rightarrow\ Safety\ Prod$

