

PRODUCT-DETAILS

## MKey8RF Die-cast M20 MKey8RF Die-cast M20 Switch



General Information	
Extended Product Type	MKey8RF Die-cast M20
Product ID	2TLA050011R0612
EAN	7350024486858
Catalog Description	MKey8RF Die-cast M20 Switch
	Solenoid safety switch with RFID technology reaching PL e or SIL 3 for the interlock function, die cast housing and stainless steel head, 3xM20 conduit entries, 24 V DC power to unlock. Safe lock function reaching PL e or SIL 3 in combination with a suitable accessory. Two safe OSSD inputs and two safe OSSD outputs. Delivered without RFID key.
Long Description	MKey are mechanical safety switches used for monitoring doors and hatches. The switch is mounted on the frame and the actuator key on the moving part of the guard. All MKey models have a safe interlocking function. Some MKey models can be locked and depending on the locking signal they can be used either as process locks or safety locks (with a safe unlocking function). MKey switches are available in different material and sizes in order to meet the requirements of different applications.

Ordering	
Minimum Order Quantity	1 piece
Customs Tariff Number	8536500700
Product Main Type	MKey
Product Name	Switch

Function	Safety mechanical switch for interlocking with locking (Safety)
Special Functions	No key supplied; With auxiliary release; RFID
Popular Downloads	
Data Sheet, Technical Information	2TLC010001C0202
Instructions and Manuals	2TLC010088M0201
Dimensions	
Product Net Depth / Length	48 mm
Product Net Height	190 mm
Product Net Width Product Net Weight	46 mm 0.8 kc
Floudet Net Weight	U.O AL
Safety Information	
Performance Level (PL)	Up to 6
Safety Integrity Level (SIL)	1 2 3
Technical	
Communication Interface	OSSE
Number of Contacts NC	
Number of Contacts NO Rated Control Supply Voltage (U <sub>S</sub> )	24 V DC
Environmental	
Ambient Air Temperature	Operation -25 40 °C
Degree of Protection  Material	IP67 Die cas
Material Compliance	
REACH Declaration  RoHS Information	2CMT2022-006480 2CMT2022-006490
Toxic Substances Control Act - TSCA	2CMT2023-006495 2CMT2023-006522
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm
Ocatification and Declarations	
Certificates and Declarations  Declaration of Conformity	No declaration needed
- CCC Declaration of Conformity - CE	2TLC010210D020
- CE Declaration of Conformity - UKCA	2TLC010211D020
<u>UL Certificate</u>	2TLC010020D0201
@ 2024 ADD All siglate sees as a	0004/04/10

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Width	65 mm
Package Level 1 Depth / Length	220 mm
Package Level 1 Height	65 mm
Package Level 1 Gross Weight	0.9 kg
Package Level 1 EAN	7350024486858

Classifications	
eClass	V11.0 : 27270611
ETIM 7	EC002593 - Position switch with guard locking
ETIM 8	EC002593 - Position switch with guard locking
ETIM 9	EC002593 - Position switch with guard locking
Object Classification Code	<u>B</u>
E-Number (Finland)	2314991
E-Number (Sweden)	3861575

## Categories

 $Low\ Voltage\ Products\ \rightarrow\ Safety\ Products\ \rightarrow\ Safety\ Products\ \rightarrow\ Safety\ Sensors,\ Switches\ and\ Locks\ \rightarrow\ MKey$ 





