HD5-B-101 1/4



PRODUCT-DETAILS

HD5-B-101

HD5-B-101 Three-Position Device



General Information

HD5-B-101 2/4

| Catalog Description | HD5-B-101 Three-Position Device |
|-----------------------|---------------------------------|
| EAN | 4013614554018 |
| Product ID | 2TLA920502R0003 |
| Extended Product Type | HD5-B-101 |

HD5-B-101 Three position device with AS-i Integrated technology. With Emergency stop button & 1 front + 2 top auxiliary buttons. Home position sensor and flashlight.

M12-5 male connector.

the operator is in the dangerous area, for example during troubleshooting, test running and programming. It can be used up to PL e/Cat 4. HD5 is developed to meet most demands of the food

and beverage industry. The housing is made of fiberglass reinforced plastic, which resists the most commonly used chemicals during cleaning in the food and beverage industry.

HD5 three-position devices are used to allow a limited movement of the machine when

Without sharp edges, there are no places where dirt and bacteria can be accumulated. The construction of the HD5 prevents condensation inside the product when subject to temperature changes in a wet environment. HD5 has IP65 rating. HD5 comes optional with two additional buttons on top of the device or with an emergency stop button.

Specific devices offer LED flashlight, a motion sensor and a home position sensor. For home position sensing the designated bracket HD5-M-001 needs to be used additionally.

| Ordering | |
|------------------------|---|
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85365019 |
| Product Main Type | HD5 |
| Product Name | Three-Position Device |
| Function | Three-position device used to allow a limited movement of the machine when the operator is in the dangerous area. Developed for the Food and Beverage industry. |
| Sub-Function | 1 front and 2 top auxiliary buttons |
| Sub-Function 2 | Flashlight Home position sensor |
| Special Functions | Emergency Stop Button |
| Status Indicator | Yes |
| Application | Suitable for Food and Beverage |

| Popular Downloads | |
|--------------------------------------|-----------------|
| Data Sheet, Technical Information | 2TLC010093L0201 |
| Instructions and Manuals | 2CDC172107D0201 |
| Dimension Diagram | 2CDC172110D0201 |
| CAD Dimensional Drawing | 2CDC001079B0201 |
| Marketing Video | 2TLC010018N0201 |

| Dimensions | |
|----------------------------|---------|
| Product Net Depth / Length | 75 mm |
| Product Net Height | 185 mm |
| Product Net Width | 55 mm |
| Product Net Weight | 0.26 kg |

Long Description

HD5-B-101 3/4

| Safety Information | |
|------------------------|--|
| Certification Agency | cULus TÜV SÜD |
| Performance Level (PL) | Up to e |
| B10d Value | Operations to Bottom Position 968 000 Operations to Middle Position 2 million |

| Technical | |
|--|---------------|
| Communication Interface | AS-i |
| Connection Configuration | M12-5 male |
| Number of Contacts CO | 2 |
| Number of Contacts NC | 0 |
| Number of Contacts NO | 0 |
| Rated Operational Current DC-12 (I _e) | (24 V) 0.02 A |
| Rated Operational Voltage | 30 V DC |

| Technical UL/CSA | |
|-----------------------|---|
| Enclosure Type UL/CSA | 1 |

| Environmental | |
|----------------------|--|
| Ambient Air | Operation -10 50 °C |
| Temperature | Storage -20 70 °C |
| Degree of Protection | IP65 |
| Material | Additional buttons: TPE |
| | Handle: Fiberglass reinforced plastic, PPH G30 |
| | Three-position button: TF4STE_B102 |

| Material Compliance | |
|---|--|
| Conflict Minerals Reporting Template (CMRT) | 9AKK108467A5658 |
| REACH Declaration | 2CMT2022-006480 |
| RoHS Information | 2CMT2022-006499 |
| RoHS Status | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| Toxic Substances Control Act - TSCA | 2CMT2023-006522 |
| WEEE B2C / B2B | Business To Business |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |

| Certificates and Declarations | |
|-------------------------------|-------------------------|
| CCC Certificate | No certification needed |
| CQC Certificate | No certification needed |

HD5-B-101 4/4

| cULus Certificate | 2TLC010050D0201 |
|-------------------------------------|------------------------------------|
| Declaration of Conformity - CCC | No declaration needed |
| Declaration of Conformity - CE | 2TLC010045D0201 |
| Declaration of Conformity - UKCA | 2TLC010191D0201 |
| TÜV Certificate | 2TLC010054D0201 2TLC010053D0201 |

| Container Information | |
|---------------------------------|---------------|
| Package Level 1 Units | box 1 piece |
| Package Level 1 Width | 300 mm |
| Package Level 1 Depth / Length | 300 mm |
| Package Level 1 Height | 60 mm |
| Package Level 1 Gross Weight | 0.26 kg |
| Package Level 1 EAN | 4013614554018 |

| Classifications | |
|-------------------------------|-----------------------------|
| eClass | V11.0 : 27371238 |
| ETIM 7 | EC002571 - Agreement switch |
| ETIM 8 | EC002571 - Agreement switch |
| ETIM 9 | EC002571 - Agreement switch |
| Object Classification Code | S |

Categories

 $Low\ Voltage\ Products\ \rightarrow\ Safety\ Products\ \rightarrow\ Safety\ Control\ Devices\ \rightarrow\ JSHD$

