



PRODUCT-DETAILS

5333

3/4IN INSUL. LIQ.TIGHT CONN STRAIGH



General Information	
Extended Product Type	5333
Product ID	7TAD012100R0007
EAN	5414363075646
Catalog Description	3/4IN INSUL. LIQ.TIGHT CONN STRAIGH
Long Description	3/4 Inch Straight Steel Insulated Liquidtight Connector

Additional Information	
Application	Used where flexible metal raceway is installed in outdoor or indoor locations where exposed to continuous or intermittent moisture.
Product Type	Connectors-Straight

Ordering	
EAN	5414363075646
UPC	786210053332

Technical	
Number of Batteries	0
Material	Steel
Size	3/4 Inch

Environmental	
WEEE Category	Product Not in WEEE Scope
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Container Information	
Package Level 1 Units	25 EA
Package Level 1 Height	101.6 mm 4 in
Package Level 1 Depth / Length	203.2 mm 8 in
Package Level 1 Width	127 mm 5 in

Certificates and Declarations	
Data Sheet, Technical Information	TDS000122
Instructions and Manuals	5333
Declaration of Conformity - CE	9AKK107492A9884

Classifications	
ETIM 8	EC001180 - Screw connection for protective metallic hose
UNSPSC	39121420

Categories	
Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Liquidtight Fittings	

