



PRODUCT-DETAILS

5333SST6
3/4 STRAIGHT 316 SS LT FITTING



| General Information | |
|-----------------------|--|
| Extended Product Type | 5333SST6 |
| Product ID | 7TAD012380R0009 |
| EAN | 5415022433296 |
| Catalog Description | 3/4 STRAIGHT 316 SS LT FITTING |
| Long Description | 3/4 Inch Liquidtight Fitting for Flexible Metallic Conduit, Straight, UL/CSA Listed, High UV Resistance, NEMA Ratings: 3, 3R, 4, 4X, Length 1.75 Inches/44.45mm, Width 1.64 Inches/41.66mm, Temperature Range 0 to 105 Degrees C, stainless steel with zinc plated steel ground cone 316 |

| Additional Information | |
|------------------------|--|
| Application | Connects Flexible Metallic Liquidtight Conduit to a Box or Enclosure |
| Product Type | Straight Fitting for Flexible Metallic Conduit |

| Ordering | |
|----------|---------------|
| EAN | 5415022433296 |
| UPC | 786210080000 |

| Technical | |
|---------------------|---|
| Number of Batteries | 0 |
| Color | Metallic |
| Material | 316 Stainless Steel with Duraplated Ground Cone |
| Size | 3/4 Inch |

| Environmental | |
|---------------|--|
| WEEE Category | Product Not in WEEE Scope |
| RoHS Status | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |

| Container Information | |
|--------------------------------|-----------------------|
| Package Level 1 Units | 10 EA |
| Package Level 1 Height | 85.725 mm 3.375 in |
| Package Level 1 Depth / Length | 133.35 mm 5.25 in |
| Package Level 1 Width | 133.35 mm 5.25 in |

| Certificates and Declarations | |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | TDS000126 |
| Instructions and Manuals | 5333SST6 |
| Declaration of Conformity - CE | 9AKK107492A9904 |

| Classifications | |
|-----------------|--|
| ETIM 8 | EC001180 - Screw connection for protective metallic hose |
| UNSPSC | 39121420 |

| Categories | |
|--|--|
| Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Liquidtight Fittings | |

