5336



PRODUCT-DETAILS

5336

1.5 INCH INSUL. LIQ.TIGHT CONN ST



Extended Product Type	533 7TAD012160R000 541436307567
Product ID EAN	
Long Description	1-1/2 Inch Straight Malleable Iron Insulated Liquidtight Connector
Additional Information Application Product Type	Used where flexible metal raceway is installed in outdoor or indoor locations where exposed to continuous or intermittent moisture.
	where exposed to continuous or intermittent moisture.
Application	where exposed to continuous or intermittent moisture.
Application Product Type	

5336

Technical	
Number of Batteries	0
Material	Malleable Iron
Size	1-1/2 Inch
<u>Environmental</u>	
WEEE Category	Product Not in WEEE Scope
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Container Information	
Package Level 1 Units	2 EA
Package Level 1 Height	76.2 mm 3 ir
Package Level 1 Depth / Length	114.3 mm 4.5 ir
Package Level 1 Width	127 mm 5 ir
Certificates and Declarations	
Data Sheet, Technical Information	TDS000122
Instructions and Manuals	5336
Declaration of Conformity - CE	9AKK107492A9884
Classifications	
ETIM 8	EC001180 - Screw connection for protective metallic hose
E I IIVI O	ECUUTIOU - Screw connection for protective metallic nose

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Installation\ Products \rightarrow Cable\ Protection,\ Explosion\ Proof\ and\ Lighting \rightarrow Liquidtight\ Fittings$

5336







