



PRODUCT-DETAILS

5341

3/8IN INSUL 45 DEGREE LIQ TIGHT CON



General Information	
Extended Product Type	5341
Product ID	7TAD012140R0005
EAN	5414363075707
Catalog Description	3/8IN INSUL 45 DEGREE LIQ TIGHT CON
Long Description	3/8 Inch 45 Degree Malleable Iron Insulated Liquidtight Connector

Additional Information	
Application	Used where flexible metal raceway is installed in outdoor or indoor locations where exposed to continuous or intermittent moisture.
Product Type	Connectors-45 Degree

Ordering	
EAN	5414363075707
UPC	786210053417

Technical	
Number of Batteries	0
Material	Malleable Iron
Size	3/8 Inch

Environmental	
WEEE Category	Product Not in WEEE Scope
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Container Information	
Package Level 1 Units	25 EA
Package Level 1 Height	109.22 mm 4.3 in
Package Level 1 Depth / Length	157.48 mm 6.2 in
Package Level 1 Width	119.38 mm 4.7 in

Certificates and Declarations	
Data Sheet, Technical Information	TDS000122
Instructions and Manuals	5341
Declaration of Conformity - CE	9AKK107492A9884

Classifications	
ETIM 8	EC001180 - Screw connection for protective metallic hose
UNSPSC	39121420

Categories	
Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Liquidtight Fittings	

