



PRODUCT-DETAILS

5341SST6  
3/8 45 DEG 316 SS LT FITTING



General Information	
Extended Product Type	5341SST6
Product ID	7TAD012420R0131
EAN	5415022450057
Catalog Description	3/8 45 DEG 316 SS LT FITTING
Long Description	3/8 Inch Liquidtight Fitting for Flexible Metallic Conduit, 45 Degree, UL/CSA Listed, High UV Resistance, NEMA Ratings: 3, 3R, 4, 4X, Length 2.18 Inches/55.37mm, Width 1.14 Inches/28.96mm, Height 1.43 Inches/36.32mm, Temperature Range 0 to 105 Degrees C, stainless steel with zinc plated steel ground cone 316

Additional Information	
Application	Connects Flexible Metallic Liquidtight Conduit to a Box or Enclosure
Product Type	45 Degree Fitting for Flexible Metallic Conduit

Ordering	
EAN	5415022450057
UPC	786210080413

<b>Technical</b>	
Number of Batteries	0
Color	Metallic
Material	316 Stainless Steel with Duraplated Ground Cone
Size	3/8 Inch

<b>Environmental</b>	
WEEE Category	Product Not in WEEE Scope
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

<b>Container Information</b>	
Package Level 1 Units	10 EA
Package Level 1 Height	85.725 mm 3.375 in
Package Level 1 Depth / Length	133.35 mm 5.25 in
Package Level 1 Width	133.35 mm 5.25 in

<b>Certificates and Declarations</b>	
Data Sheet, Technical Information	TDS000126
Instructions and Manuals	5341SST6
Declaration of Conformity - CE	9AKK107492A9904

<b>Classifications</b>	
ETIM 8	EC001180 - Screw connection for protective metallic hose
UNSPSC	39121420

<b>Categories</b>	
Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Liquidtight Fittings	

