



 PRODUCT-DETAILS

5342

1/2 IN INSUL 45 DEG LIQ TIGHT CON



General Information

Extended Product Type	5342
Product ID	7TAD012130R0004
EAN	5414363075714
Catalog Description	1/2 IN INSUL 45 DEG LIQ TIGHT CON
Long Description	1/2 Inch 45 Degree Malleable Iron Insulated Liquidtight Connector

Additional Information

Application	Used where flexible metal raceway is installed in outdoor or indoor locations where exposed to continuous or intermittent moisture.
Product Type	Connectors-45 Degree

Ordering

EAN	5414363075714
UPC	786210053424

Technical

Number of Batteries	0
Material	Malleable Iron
Size	1/2 Inch

Environmental

WEEE Category	Product Not in WEEE Scope
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Container Information

Package Level 1 Units	25 EA
Package Level 1 Height	101.6 mm 4 in
Package Level 1 Depth / Length	203.2 mm 8 in
Package Level 1 Width	127 mm 5 in

Certificates and Declarations

Data Sheet, Technical Information	TDS000122
Instructions and Manuals	5342
Declaration of Conformity - CE	9AKK107492A9884

Classifications

ETIM 8	EC001180 - Screw connection for protective metallic hose
UNSPSC	39121420

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Liquidtight Fittings

