



PRODUCT-DETAILS

5343

3/4IN INSUL 45 DEGREE LIQ TIGHT CON



General Information	
Extended Product Type	5343
Product ID	7TAD012140R0006
EAN	5414363075721
Catalog Description	3/4IN INSUL 45 DEGREE LIQ TIGHT CON
Long Description	3/4 Inch 45 Degree Malleable Iron Insulated Liquidtight Connector

Additional Information	
Application	Used where flexible metal raceway is installed in outdoor or indoor locations where exposed to continuous or intermittent moisture.
Product Type	Connectors-45 Degree

Ordering	
EAN	5414363075721
UPC	786210053431

<b>Technical</b>	
Number of Batteries	0
Material	Malleable Iron
Size	3/4 Inch

<b>Environmental</b>	
WEEE Category	Product Not in WEEE Scope
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

<b>Container Information</b>	
Package Level 1 Units	10 EA
Package Level 1 Height	101.6 mm 4 in
Package Level 1 Depth / Length	152.4 mm 6 in
Package Level 1 Width	114.3 mm 4.5 in

<b>Certificates and Declarations</b>	
Data Sheet, Technical Information	TDS000122
Instructions and Manuals	5343
Declaration of Conformity - CE	9AKK107492A9884

<b>Classifications</b>	
ETIM 8	EC001180 - Screw connection for protective metallic hose
UNSPSC	39121420

<b>Categories</b>	
Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Liquidtight Fittings	

