5343SST6 1/3



PRODUCT-DETAILS

5343SST6 3/4 45 DEG 316 SS LT FITTING



General Information	
Extended Product Type	5343SST6
Product ID	7TAD012390R0021
EAN	5415022433302
Catalog Description	3/4 45 DEG 316 SS LT FITTING
Long Description	3/4 Inch Liquidtight Fitting for Flexible Metallic Conduit, 45 Degree, UL/CSA Listed, High UV Resistance, NEMA Ratings: 3, 3R, 4, 4X, Length 2.70 Inches/68.58mm, Width 1.64 Inches/41.66mm, Height 2.10 Inches/53.34mm, Temperature Range 0 to 105 Degrees C, stainless steel with zinc plated steel ground cone 316
Additional Information	
	Connecte Florible Metallic Liquidiaht Conduit to a Pay or Frelegue
Application	Connects Flexible Metallic Liquidtight Conduit to a Box or Enclosure
	Connects Flexible Metallic Liquidtight Conduit to a Box or Enclosure 45 Degree Fitting for Flexible Metallic Conduit
Application	. 5
Application Product Type	. 5

5343SST6 2/3

Technical	
Number of Batteries	C
Color	Metallic
Material	316 Stainless Steel with Duraplated Ground Cone
Size	3/4 Inch
Environmental	
WEEE Category	Product Not in WEEE Scope
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Container Information	
Package Level 1 Units	10 EA
Package Level 1 Height	85.725 mm 3.375 in
Package Level 1 Depth / Length	133.35 mm 5.25 in
Package Level 1 Width	133.35 mm 5.25 in
Certificates and Declarations	
Data Sheet, Technical Information	TDS000126
Instructions and Manuals	5343SST6
Declaration of Conformity - CE	9AKK107492A9904
Classifications	
ETIM 8	EC001180 - Screw connection for protective metallic hose
UNSPSC	39121420

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Installation\ Products \rightarrow Cable\ Protection,\ Explosion\ Proof\ and\ Lighting \rightarrow Liquidtight\ Fittings$

5343SST6 3/3

