



PRODUCT-DETAILS

5344

1 IN INSUL 45 DEGREE LIQ TIGHT CON



General Information	
Extended Product Type	5344
Product ID	7TAD012140R0008
EAN	5414363075738
Catalog Description	1 IN INSUL 45 DEGREE LIQ TIGHT CON
Long Description	1 Inch 45 Degree Malleable Iron Insulated Liquidtight Connector

Additional Information	
Application	Used where flexible metal raceway is installed in outdoor or indoor locations where exposed to continuous or intermittent moisture.
Product Type	Connectors-45 Degree

Ordering	
EAN	5414363075738
UPC	786210053448

Technical	
Number of Batteries	0
Material	Malleable Iron
Size	1 Inch

Environmental	
WEEE Category	Product Not in WEEE Scope
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Container Information	
Package Level 1 Units	5 EA
Package Level 1 Height	101.6 mm 4 in
Package Level 1 Depth / Length	152.4 mm 6 in
Package Level 1 Width	114.3 mm 4.5 in

Certificates and Declarations	
Data Sheet, Technical Information	TDS000122
Instructions and Manuals	5344
Declaration of Conformity - CE	9AKK107492A9884

Classifications	
ETIM 8	EC001180 - Screw connection for protective metallic hose
UNSPSC	39121420

Categories	
Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Liquidtight Fittings	

