



PRODUCT-DETAILS

5347

2 IN INSUL 45 DEGREE LIQ TIGHT CONN



General Information	
Extended Product Type	5347
Product ID	7TAD012170R0010
EAN	5414363099994
Catalog Description	2 IN INSUL 45 DEGREE LIQ TIGHT CONN
Long Description	2 Inch 45 Degree Malleable Iron Insulated Liquidtight Connector

Additional Information	
Application	Used where flexible metal raceway is installed in outdoor or indoor locations where exposed to continuous or intermittent moisture.
Product Type	Connectors-45 Degree

Ordering	
EAN	5414363099994
UPC	786210053479

<b>Technical</b>	
Number of Batteries	0
Material	Malleable Iron
Size	2 Inch

<b>Environmental</b>	
WEEE Category	Product Not in WEEE Scope
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

<b>Container Information</b>	
Package Level 1 Units	1 EA
Package Level 1 Height	101.6 mm 4 in
Package Level 1 Depth / Length	152.4 mm 6 in
Package Level 1 Width	114.3 mm 4.5 in

<b>Certificates and Declarations</b>	
Data Sheet, Technical Information	TDS000122
Instructions and Manuals	5347
Declaration of Conformity - CE	9AKK107492A9884

<b>Classifications</b>	
ETIM 8	EC001180 - Screw connection for protective metallic hose
UNSPSC	39121420

<b>Categories</b>	
Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Liquidtight Fittings	

