



PRODUCT-DETAILS

5352SST6
1/2 90 DEG 316 SS LT FITTING



General Information	
Extended Product Type	5352SST6
Product ID	7TAD012980R0326
EAN	5415022450361
Catalog Description	1/2 90 DEG 316 SS LT FITTING
Long Description	1/2 Inch Liquidtight Fitting for Flexible Metallic Conduit, 90 Degree, UL/CSA Listed, High UV Resistance, NEMA Ratings: 3, 3R, 4, 4X, Length 2.35 Inches/59.69mm, Width 1.33 Inches/33.78mm, Height 2.25 Inches/57.15mm, Temperature Range 0 to 105 Degrees C, stainless steel with zinc plated steel ground cone 316

Additional Information	
Application	Connects Flexible Metallic Liquidtight Conduit to a Box or Enclosure
Product Type	90 Degree Fitting for Flexible Metallic Conduit

Ordering	
EAN	5415022450361
UPC	786210080864

Technical	
Number of Batteries	0
Color	Metallic
Material	316 Stainless Steel with Duraplated Ground Cone
Size	1/2 Inch

Environmental	
WEEE Category	Product Not in WEEE Scope
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Container Information	
Package Level 1 Units	10 EA
Package Level 1 Height	85.725 mm 3.375 in
Package Level 1 Depth / Length	133.35 mm 5.25 in
Package Level 1 Width	133.35 mm 5.25 in

Certificates and Declarations	
Data Sheet, Technical Information	TDS000126
Instructions and Manuals	5352SST6
Declaration of Conformity - CE	9AKK107492A9904

Classifications	
ETIM 8	EC001180 - Screw connection for protective metallic hose
UNSPSC	39121420

Categories	
Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Liquidtight Fittings	

