



---

**PRODUCT-DETAILS****5354****1 IN INSUL 90 DEGREE LIQ TIGHT CON**

---

**General Information**

Extended Product Type	5354
Product ID	7TAD012140R0013
EAN	5414363075790
Catalog Description	1 IN INSUL 90 DEGREE LIQ TIGHT CON
Long Description	1 Inch 90 Degree Malleable Iron Insulated Liquidtight Connector

---

**Additional Information**

Application	Used where flexible metal raceway is installed in outdoor or indoor locations where exposed to continuous or intermittent moisture.
Product Type	Connectors-90 Degree

---

**Ordering**

EAN	5414363075790
UPC	786210053547

---

**Technical**

---

Number of Batteries	0
Material	Malleable Iron
Size	1 Inch

---

**Environmental**

---

WEEE Category	Product Not in WEEE Scope
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

---

**Container Information**

---

Package Level 1 Units	5 EA
Package Level 1 Height	101.6 mm 4 in
Package Level 1 Depth / Length	152.4 mm 6 in
Package Level 1 Width	114.3 mm 4.5 in

---

**Certificates and Declarations**

---

Data Sheet, Technical Information	TDS000122
Instructions and Manuals	5354
Declaration of Conformity - CE	9AKK107492A9884

---

**Classifications**

---

ETIM 8	EC001180 - Screw connection for protective metallic hose
UNSPSC	39121420

---

**Categories**

---

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Liquidtight Fittings

