



---

**PRODUCT-DETAILS****5355****1.25 IN INSUL 90 DEG LIQ TIGHT CONN**

---

**General Information**

Extended Product Type	5355
Product ID	7TAD012170R0012
EAN	5414363075806
Catalog Description	1.25 IN INSUL 90 DEG LIQ TIGHT CONN
Long Description	1-1/4 Inch 90 Degree Malleable Iron Insulated Liquidtight Connector

---

**Additional Information**

Application	Used where flexible metal raceway is installed in outdoor or indoor locations where exposed to continuous or intermittent moisture.
Product Type	Connectors-90 Degree

---

**Ordering**

EAN	5414363075806
UPC	786210053554

**Technical**

Number of Batteries	0
Material	Malleable Iron
Size	1-1/4 Inch

**Environmental**

WEEE Category	Product Not in WEEE Scope
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

**Container Information**

Package Level 1 Units	5 EA
Package Level 1 Height	114.3 mm 4.5 in
Package Level 1 Depth / Length	241.3 mm 9.5 in
Package Level 1 Width	165.1 mm 6.5 in

**Certificates and Declarations**

Data Sheet, Technical Information	TDS000122
Instructions and Manuals	5355
Declaration of Conformity - CE	9AKK107492A9884

**Classifications**

ETIM 8	EC001180 - Screw connection for protective metallic hose
UNSPSC	39121420

**Categories**

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Liquidtight  
Fittings

