DP4-1-625 1/3



PRODUCT-DETAILS

## **DP4-1-625**

## DP4-1-625 ABB-free@homeTouch 4.3"



General Information	
Extended Product Type	DP4-1-625
Product ID	2CKA006220A0120
EAN	4011395180198
Catalog Description	DP4-1-625 ABB-free@homeTouch 4.3"
Long Description	For the central control of up to 16 configurable ABB-free@home® functions. For the display of configurable system messages. A configurable primary function can be triggered with a multi-touch gesture. Capacitive touch screen with closed glass surface. With integrated room temperature controller and temperature sensor. In connection with temperature sensor 6226/T the integrated room temperature controller can be fitted with a remote sensor. Suitable as room temperature controller extension unit (up to 8). Requires additional power supply 24 VDC e.g. 6358-101. Power consumption: 150 mA Display size: 10.9 cm (4.3") Display resolution: 480 x 854 Mounting height: 8 mm

Installation	
Instructions and Manuals	No document needed
Mounting Type	Flush Mounted

DP4-1-625 2/3

Technical	
Data Sheet, Technical Information	2CKA001373B9087
Compatible Bus Systems	free@home (TP)
Product Range	free@home
Number of Batteries	0
 Design	
Surface Finishing	Untreated Glossy
Material	Thermoplastic
Color	black
Material Compliance	
RoHS Information	2CKA200000E4917
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
REACH Declaration	2CKA309999E9999
REACH Information	True - contains substances > 0.1 mass percentage
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363
· · ·	
SCIP	3aeee31f-349c-4ff8-b11c-45eac332ff94 Germany (DE)
Environmental Ambient Air	
Environmental	Operation -5 +40 °C
Environmental Ambient Air Temperature	Operation -5 +40 °C
Environmental  Ambient Air Temperature Degree of Protection  Dimensions	Operation -5 +40 °C
Environmental  Ambient Air Temperature Degree of Protection  Dimensions Product Net Weight	Operation -5 +40 °C IP20 0.5 kg
Environmental  Ambient Air Temperature Degree of Protection	Operation -5 +40 °C IP20 0.5 kg 50 mm
Environmental  Ambient Air Temperature Degree of Protection  Dimensions Product Net Weight Built-In Depth (t <sub>2</sub> )	Operation -5 +40 °C IP20 0.5 kg 50 mm
Environmental  Ambient Air Temperature Degree of Protection  Dimensions Product Net Weight Built-In Depth (t <sub>2</sub> ) Screen Size	3aeee31f-349c-4ff8-b11c-45eac332ff94 Germany (DE)  Operation -5 +40 °C  IP20  0.5 kg 50 mm 4.3 in
Environmental  Ambient Air Temperature Degree of Protection  Dimensions Product Net Weight Built-In Depth (t <sub>2</sub> ) Screen Size  Certificates and Declarations	Operation -5 +40 °C IP20 0.5 kg 50 mm 4.3 in
Environmental  Ambient Air Temperature Degree of Protection  Dimensions Product Net Weight Built-In Depth (t <sub>2</sub> ) Screen Size  Certificates and Declarations Declaration of Conformity - CE	Operation -5 +40 °C IP20 0.5 kg 50 mm 4.3 in
Environmental  Ambient Air Temperature  Degree of Protection  Dimensions  Product Net Weight  Built-In Depth (t <sub>2</sub> )  Screen Size  Certificates and Declarations  Declaration of Conformity - CE  Classifications	Operation -5 +40 °C IP20  0.5 kg 50 mm 4.3 in
Environmental  Ambient Air Temperature Degree of Protection  Dimensions Product Net Weight Built-In Depth (t <sub>2</sub> ) Screen Size  Certificates and Declarations Declaration of Conformity - CE  Classifications ETIM 9	Operation -5 +40 °C  IP20  0.5 kg 50 mm 4.3 in  DEBJE-2CKA006220A0120-ROHS
Environmental  Ambient Air Temperature Degree of Protection  Dimensions Product Net Weight Built-In Depth (t <sub>2</sub> ) Screen Size  Certificates and Declarations Declaration of	Operation -5 +40 °C IP20  0.5 kg 50 mm 4.3 in

DP4-1-625 3/3

## Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Building\ and\ Home\ Automation\ Solutions \rightarrow free@home \rightarrow Visualisation,\ Display\ and\ Signalling \rightarrow Touch\ Panels$ 









3605