




PRODUCT-DETAILS

7360  
5/16 INSUL. LIQ. TIGHT CONN.



General Information	
Extended Product Type	7360
Product ID	7TAD012330R0024
EAN	5414363076032
Catalog Description	5/16 INSUL. LIQ. TIGHT CONN.
Long Description	5/16 Inch Steel Insulated Liquidtight Connector With PG Thread and Chromate Finish, Thread Size 9

Additional Information	
Application	Nylon Insulated Straight Fittings
Product Type	Liquidtight Flexible Metal Conduit Fittings

Ordering	
EAN	5414363076032
UPC	786210073606

<b>Technical</b>	
Number of Batteries	0
Material	Nylon Insulated
Size	5/16 Inch

<b>Environmental</b>	
WEEE Category	Product Not in WEEE Scope
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

<b>Container Information</b>	
Package Level 1 Units	25 EA
Package Level 1 Height	76.2 mm 3 in
Package Level 1 Depth / Length	127 mm 5 in
Package Level 1 Width	114.3 mm 4.5 in

<b>Certificates and Declarations</b>	
Data Sheet, Technical Information	7360
Instructions and Manuals	7360

<b>Classifications</b>	
ETIM 8	EC001180 - Screw connection for protective metallic hose
UNSPSC	39121420

<b>Categories</b>	
Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Liquidtight Fittings	

