



---

**PRODUCT-DETAILS**

## **S800-SOR12**

### S800-SOR12 Shunt Operation Release



---

**General Information**

|                       |  |
|-----------------------|--|
| Extended Product Type | S800-SOR12   |
| Product ID            | 2CCS800900R0201  |
| EAN                   | 7612271212070  |
| Catalog Description   | S800-SOR12 Shunt Operation Release   |
| Long Description      | <p>The S800-SOR12 is a 12V shunt opening release is for remote release of the S800 High Performance MCB using an electrical impulse. Operation of the trigger is guaranteed at a voltage between 70% and 110% of the rated voltage <math>U_n</math> - both for AC and DC. The S800-SOR12 can be mounted by the user at the left side of S800 High Performance MCB.</p> |

---

**Technical**

|              |  |
|--------------|--|
| Standards    | IEC/EN 60947-2   |
| Suitable For | S800S<br>S800N<br>S800C<br>S800B<br>S800HV<br>S800U<br>S800PV-SP |

|                                   |  |
|-----------------------------------|--|
|                                   | S800PV-SD<br>S800PV-M-H  |
| Rated Operational Voltage         | 12 V AC/DC   |
| Rated Insulation Voltage (Ui)     | 690 V AC   |
| Rated Control Supply Voltage (Us) | (50 Hz) 12...12 V<br>(50 Hz) 12...12 V<br>(60 Hz) 12...12 V<br>(60 Hz) 12...12 V<br>(DC) 12...12 V<br>(DC) 12...12 V |
| Rated Frequency (f)               | 50...60 Hz   |
| Power Loss                        | 15.5 W   |
| Number of Contacts CO             | 0  |
| Number of Contacts NC             | 0  |
| Number of Contacts NO             | 1  |
| Tightening Torque                 | 3.5 N·m  |
| Actuator Marking                  | I / O  |
| Mounting on DIN Rail              | TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715<br>TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715       |
| Mounting Position                 | Any  |
| Recommended Screw Driver          | Pozidriv 2   |
| Connecting Capacity               | Flexible 1 ... 25 mm <sup>2</sup><br>Stranded 1 ... 35 mm <sup>2</sup>   |
| Terminal Type                     | Screw Terminals  |

## Material Compliance

|   |                                    |
|---|------------------------------------|
| RoHS Information                            | 2CCC413003D0201<br>9AKK107680A3903 |
| RoHS Status                                 | Following EU Directive 2011/65/EU  |
| RoHS Date                                   | 20170426                           |
| Conflict Minerals Reporting Template (CMRT) | 9AKK108468A3363                    |

## Environmental

|                           |  |
|---------------------------|--|
| Ambient Air Temperature   | Operation -25 ... +60 °C<br>Storage -40 ... +70 °C |
| Degree of Protection      | acc. to IEC 60529 IP20                             |
| Environmental Information | 2CCY413207D0203                                    |

## Dimensions

|                            |                 |
|----------------------------|-----------------|
| Product Net Width          | 27 mm           |
| Product Net Height         | 95 mm           |
| Product Net Depth / Length | 82.5 mm         |
| Product Net Weight         | 150 g           |
| Dimension Diagram          | 2CCC413003C0201 |

---

## Ordering

---

|                              |             |
|------------------------------|-------------|
| Package Level 1 Units        | box 1 piece |
| Package Level 1 Gross Weight | 170 g       |
| E-Number (Finland)           | 3212431     |

---

---

## Certificates and Declarations

---

|                                |                 |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 2CCC413003D0201 |
|--------------------------------|-----------------|

---

---

## Installation

---

|                          |                 |
|--------------------------|-----------------|
| Instructions and Manuals | 9AKK106930A3418 |
|--------------------------|-----------------|

---

---

## Popular Downloads

---

|                                   |                 |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 2CCC413003C0208 |
|-----------------------------------|-----------------|

---

---

## Classifications

---

|                                    |  |
|------------------------------------|--|
| ETIM 8                             | EC001023 - Shunt release (for power circuit breaker)       |
| ETIM 9                             | EC001023 - Shunt release (for power circuit breaker)       |
| WEEE Category                      | 5. Small Equipment (No External Dimension More Than 50 cm) |
| WEEE B2C / B2B                     | Business To Business                                       |
| CN8                                | 85389040   |
| UNSPSC                             | 39121601   |
| eClass                             | V11.0 : 27370418   |
| IDEA Granular Category Code (IGCC) | 4879 >> Shunt release (for power circuit breaker)          |
| Object Classification Code         | F  |

---

---

## Categories

---

Low Voltage Products and Systems → Modular DIN Rail Products → High Performance Circuit Breakers HPCBs → High Performance Circuit Breakers HPCBs Accessories

