BS9 3/12 1/3



PRODUCT-DETAILS

BS9 3/12 BS9 3/12 Busbar 3 phase



BS9 3/12
2CSL930001R1012
8012542047551
BS9 3/12 Busbar 3 phase
usbar for SN201 MCBs. Maximum rated current: 60A. Cross section 10 mm2, 3 phases, 12 pins

Eco Transparency	
Environmental Product Declaration - EPD	No declaration needed

Technical		
Suitable For	SN201	
Suitable for Product Class	Miniature circuit breakers MCBs	
Rated Operational Voltage	400 V	
Rated Short-time Withstand Current Low	25 kA	

BS9 3/12 2/3

Voltage (I)	
Voltage (I _{cw}) Rated Uninterrupted	63 A
Current (I _u)	
Pitch	44698_MMT\$
Number of Poles	12
Number of Phases	3
Number of Mountable Devices	4
Connection Type	Pin
Rated Cross-Section	10 mm²
Material Compliance	
RoHS Information	2CSC400003D2701
RoHS Status	Following EU Directive 2011/65/EU
RoHS Date	20190722
REACH Declaration	9AKK108468A9644
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363
Environmental	
Environmental Information	document not needed
Dimensions	
Product Net Width	0.211 m
Product Net Height	0.280 m
Product Net Depth /	0.150 m
Length	
Product Net Weight	0.090 kg
Ordering	
Package Level 1 Units	bag 5 piece
Package Level 1 Gross Weight	0.450 kg
E-Number (Finland)	3210878
Certificates and Declarations	
Declaration of Conformity	2CSC400003D2701
<u>- CE</u>	
Installation	
Instructions and Manuals	No document needed
Popular Downloads	
Data Sheet, Technical	2CSC400002D0210
Information	

BS9 3/12 3/3

Classifications	
ETIM 8	EC000215 - Phase busbar
ETIM 9	EC000215 - Phase busbar
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	85389099
eClass	V11.0 : 27371306
Object Classification Code	Q

Categories

 $Low\ Voltage\ Products\ and\ Systems\ \rightarrow\ Modular\ DIN\ Rail\ Products\ \rightarrow\ Miniature\ Circuit\ Breakers\ MCBs\ \rightarrow\ Miniature\ Circuit\ Breakers\ MCBs\ Accessories\ \rightarrow\ Busbars\ and\ Accessories\ (IEC\ Range)$





