



PRODUCT-DETAILS

A41 412-100

A41 412-100, Energy meter'Gold', Modbus RS485, Single-phase, 5 A



General Information	
Extended Product Type	A41 412-100
Product ID	2CMA170505R1000
ABB Type Designation	A41 412-100
EAN	7392696705059
Catalog Description	A41 412-100, Energy meter'Gold', Modbus RS485, Single-phase, 5 A
Long Description	Advanced DIN-rail meter with a large and easy to read back lighted pixel-oriented display. The meter is intended for use in the industry, commercial buildings etc. The meter can be used in 3 or 4 wire systems with a wide voltage range. The meter has several instrumentation values, 25 possible alarms and event logs. Single phase direct connected for active energy. One output for pulses or alarm etc. Accuracy class 1.0 (or B for MID meters). The meters is IEC approved + MID approved and verified.

Eco Transparency	
Environmental Product Declaration - EPD	9AKK108467A4138

Technical	
Standards	EN 50470-1
Function	Electricity meter
Sub-Function	Gold
Rated Voltage (U _r)	57.7-288 V
Voltage Range	47...331 V
Rated Current (I _n)	5 A
	Maximum 80 A
Current Rating	5 A
Rated Frequency (f)	50 / 60 Hz
	0.807 W
Communication Interface	Modbus RS485
Accuracy	Active Energy Class B MID (±1%)
Measuring Instrument Conformity	Measurement Instrument Directive (MID)
Meter Tariff Control	Internal
	External
Meter Tariff Rating	Multi-Tariff
Pulse Output Rate	1-999999
Number of Poles	1
Number of Phases	Single-phases
Number of Counter Positions	7
Number of Digital In/Outputs	2 DI 2 DO
Real-time Clock	Real time clock with 5 ppm accuracy at reference temperature 25°C
Meter Type	Direct connected
Mounting Type	DIN-Rail
Pulse Output Type	Electrical
Type of Indicator	Digital
Enclosure Material	Polycarbonate in transparent front glass. Glass reinforced polycarbonate in bottom case and upper case. Polycarbonate in terminal cover.
I/O Option	2 digital output, 2 digital input
Communication	Modbus RTU
Connecting Capacity Main Circuit	1 ... 25 mm²

Material Compliance	
RoHS Information	2CMC484006
RoHS Status	Following EU Directive 2002/95/EC August 18, 2005 and amendment
RoHS Date	2011-44
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Environmental	
Ambient Air Temperature	Operation -40 ... 70 °C
Degree of Protection	IP20
Environmental Information	2CMC484004D0001

Dimensions	
Width in Number of Modular Spacings	4
Product Net Width	70 mm
Product Net Height	26.5 mm
Product Net Depth / Length	65 mm
Product Net Weight	0.246 kg
Size	97X70X65

Ordering	
Package Level 1 Units	box 1 piece
Package Level 1 Gross Weight	0.318 kg
E-Number (Finland)	6701008
E-Number (Sweden)	0980686

Certificates and Declarations	
Declaration of Conformity - CE	2CMC484003D0001

Installation	
Instructions and Manuals	2CMC484004M0201

Popular Downloads	
Data Sheet, Technical Information	2CMC484002M0201

Classifications	
ETIM 8	EC001506 - Kilowatt-hour meter
ETIM 9	EC001506 - Kilowatt-hour meter
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	90283011
eClass	V11.0 : 27142316
Object Classification Code	P

Accessories	
-------------	--

Identifier	Description	Type	Quantity	Unit Of Measure
2CCG000242R0001	SCU100 Control unit	SCU100	1	piece
2CDG110226R0011	QA/S3.16.1 Energy Analyzer, M-Bus, 16 Devices, MDRC	QA/S3.16.1	1	piece
2CDG110227R0011	QA/S3.64.1 Energy Analyzer, M-Bus, 64 Devices, MDRC	QA/S3.64.1	1	piece
2CDG110228R0011	QA/S4.16.1 Energy Analyzer, Modbus RTU, 16 Devices, MDRC	QA/S4.16.1	1	piece
2CDG110229R0011	QA/S4.64.1 Energy Analyzer, Modbus RTU, 64 Devices, MDRC	QA/S4.64.1	1	piece
2CDG110224R0011	QA/S1.16.1 Energy Analyzer, KNX, 16 Devices, MDRC	QA/S1.16.1	1	piece

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Energy Efficiency Devices → Energy Meters

