



PRODUCT-DETAILS

A44 552-100

A44 552-100, Energy meter'Platinum', Modbus RS485, Three-phase, 1 A



General Information	
Extended Product Type	A44 552-100
Product ID	2CMA170545R1000
ABB Type Designation	A44 552-100
EAN	7392696705455
Catalog Description	A44 552-100, Energy meter'Platinum', Modbus RS485, Three-phase, 1 A
Long Description	Advanced DIN-rail meter with a large and easy to read back lighted pixel-oriented display. The meter is intended for use in the industry, commercial buildings etc. The meter can be used in 3 or 4 wire systems with a wide voltage range. The meter has several instrumentation values, 25 possible alarms and event logs. Three phase transformer connectedfor active and reactive energy. Import and export of energy in different registers and one total. Resettable register for intermediate values. Internal clock for tariff shift, Min and maximum demand, previous values and event log with timestamps. 8 channel load profile Four programmable inputs or outputs. Up to the 16th harmonicsfor pulses or alarm etc. RS-485 communication over Modbus RTU or EQ Bus. Accuracy class 0,5 (or C for MID meters). The meters is IEC approved + MID approved and verified.

Eco Transparency	
Environmental Product	9AKK108467A4138

Declaration - EPD

Technical		
Standards	IEC 62052-11	
Function	Electricity meter	
Sub-Function	Platinum	
Rated Voltage (U _r)	3x57.7-288 V	
Voltage Range	3x47...331 V	
Rated Current (I _n)	1 A Maximum 6 A	
Current Rating	1 A	
Rated Frequency (f)	50 / 60 Hz	
	0.801 W	
Communication Interface	Modbus RS485	
Accuracy	Active Energy Class C MID (±0.5%)	
Measuring Instrument Conformity	Measurement Instrument Directive (MID)	
Meter Tariff Control	Internal External	
Meter Tariff Rating	Multi-Tariff	
Pulse Output Rate	1-999999	
Number of Poles	4	
Number of Phases	Three-phase	
Number of Counter Positions	7	
Number of Digital In/Outputs	4 I/O Channels	
Real-time Clock	Real time clock with 5 ppm accuracy at reference temperature 25°C	
Meter Type	Transformer connected	
Mounting Type	DIN-Rail	
Pulse Output Type	Electrical	
Type of Indicator	Digital	
Enclosure Material	Polycarbonate in transparent front glass. Glass reinforced polycarbonate in bottom case and upper case. Polycarbonate in terminal cover.	
I/O Option	4 programmable I/O	
Additional Information	CT (1A, 5A)	
Communication	Modbus RTU	
Connecting Capacity Main Circuit	0.5 ... 10 mm²	

Material Compliance		
RoHS Information	2CMC484006	
RoHS Status	Following EU Directive 2002/95/EC August 18, 2005 and amendment	
RoHS Date	2011-44	
REACH Declaration	9AKK108467A9482	
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363	

Environmental		
Ambient Air	Operation -40 ... 70 °C	

Temperature	
Degree of Protection	IP20
Environmental Information	2CMC484005D0001

Dimensions

Width in Number of Modular Spacings	7
Product Net Width	123 mm
Product Net Height	26.5 mm
Product Net Depth / Length	65 mm
Product Net Weight	0.363 kg
Size	97X123X65
Dimension Diagram	2CMC484001M0201

Ordering

Package Level 1 Units	box 1 piece
Package Level 1 Gross Weight	0.453 kg
E-Number (Finland)	6625021
E-Number (Sweden)	0980727

Certificates and Declarations

Declaration of Conformity - CE	2CMC484002D0001
--------------------------------	-----------------

Installation

Instructions and Manuals	2CMC484003M0201
--------------------------	-----------------

Popular Downloads

Data Sheet, Technical Information	2CMC484001M0201
-----------------------------------	-----------------

Classifications

ETIM 8	EC001506 - Kilowatt-hour meter
ETIM 9	EC001506 - Kilowatt-hour meter
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	90283019
eClass	V11.0 : 27142316
Object Classification Code	P

Accessories

Identifier	Description	Type	Quantity	Unit Of Measure
2CSG225995R1101	CT MAX 1000 Current transformer	CT MAX 1000	1	piece
2CSG226055R1101	CT MAX 1000 SELV Current transformer	CT MAX 1000 SELV	1	piece
2CSG225945R1101	CT MAX 300 Current transformer	CT MAX 300	1	piece
2CSG226005R1101	CT MAX 300 SELV Current transformer	CT MAX 300 SELV	1	piece
2CSG225955R1101	CT MAX 400 Current transformer	CT MAX 400	1	piece
2CSG226015R1101	CT MAX 400 SELV Current transformer	CT MAX 400 SELV	1	piece
2CSG225965R1101	CT MAX 500 Current transformer	CT MAX 500	1	piece
2CSG226025R1101	CT MAX 500 SELV Current transformer	CT MAX 500 SELV	1	piece
2CSG225975R1101	CT MAX 600 Current transformer	CT MAX 600	1	piece
2CSG226035R1101	CT MAX 600 SELV Current transformer	CT MAX 600 SELV	1	piece
2CSG225985R1101	CT MAX 800 Current transformer	CT MAX 800	1	piece
2CSG226045R1101	CT MAX 800 SELV Current transformer	CT MAX 800 SELV	1	piece
2CSG225785R1101	CT PRO XT 100 Current transformer	CT PRO XT 100	1	piece
2CSG225885R1101	CT PRO XT 100 SELV Current transformer	CT PRO XT 100 SELV	1	piece
2CSG225795R1101	CT PRO XT 150 Current transformer	CT PRO XT 150	1	piece
2CSG225895R1101	CT PRO XT 150 SELV Current transformer	CT PRO XT 150 SELV	1	piece
2CSG225805R1101	CT PRO XT 200 Current transformer	CT PRO XT 200	1	piece
2CSG225905R1101	CT PRO XT 200 SELV Current transformer	CT PRO XT 200 SELV	1	piece
2CSG225815R1101	CT PRO XT 250 Current transformer	CT PRO XT 250	1	piece
2CSG225915R1101	CT PRO XT 250 SELV Current transformer	CT PRO XT 250 SELV	1	piece
2CSG225825R1101	CT PRO XT 300 Current transformer	CT PRO XT 300	1	piece
2CSG225925R1101	CT PRO XT 300 SELV Current transformer	CT PRO XT 300 SELV	1	piece
2CSG225745R1101	CT PRO XT 40 Current transformer	CT PRO XT 40	1	piece
2CSG225845R1101	CT PRO XT 40 SELV Current transformer	CT PRO XT 40 SELV	1	piece
2CSG225835R1101	CT PRO XT 400 Current transformer	CT PRO XT 400	1	piece
2CSG225935R1101	CT PRO XT 400 SELV Current transformer	CT PRO XT 400 SELV	1	piece
2CSG225755R1101	CT PRO XT 50 Current transformer	CT PRO XT 50	1	piece
2CSG225855R1101	CT PRO XT 50 SELV Current transformer	CT PRO XT 50 SELV	1	piece
2CSG225765R1101	CT PRO XT 60 Current transformer	CT PRO XT 60	1	piece
2CSG225865R1101	CT PRO XT 60 SELV Current transformer	CT PRO XT 60 SELV	1	piece
2CSG225775R1101	CT PRO XT 80 Current transformer	CT PRO XT 80	1	piece
2CSG225875R1101	CT PRO XT 80 SELV Current transformer	CT PRO XT 80 SELV	1	piece
2CCG000242R0001	SCU100 Control unit	SCU100	1	piece
2CDG110226R0011	QA/S3.16.1 Energy Analyzer, M-Bus, 16 Devices, MDRC	QA/S3.16.1	1	piece

2CDG110227R0011	QA/S3.64.1 Energy Analyzer, M-Bus, 64 Devices, MDRC	QA/S3.64.1	1	piece
2CDG110228R0011	QA/S4.16.1 Energy Analyzer, Modbus RTU, 16 Devices, MDRC	QA/S4.16.1	1	piece
2CDG110229R0011	QA/S4.64.1 Energy Analyzer, Modbus RTU, 64 Devices, MDRC	QA/S4.64.1	1	piece
2CDG110224R0011	QA/S1.16.1 Energy Analyzer, KNX, 16 Devices, MDRC	QA/S1.16.1	1	piece

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Energy Efficiency Devices → Energy Meters

