



PRODUCT-DETAILS

# AD1NO-15m

## AD1NO-15m Analog Time switch



| General Information   |   |
|-----------------------|---|
| Extended Product Type | AD1NO-15m   |
| Product ID            | 2CSM222471R1000   |
| EAN                   | 8012542224716   |
| Catalog Description   | AD1NO-15m Analog Time switch  |
| Long Description      | Analog time switch, daily prorammig, 1 channel NO, 15 minutes switch, without reserve |

| Technical                 |   |
|---------------------------|---|
| Standards                 | EN 60730-2-7  |
| Function                  | Daily   |
| Rated Operational Voltage | 230 V   |
| Operational Voltage       | Maximum (Incl. Tolerance) 195 V AC<br>Maximum (Incl. Tolerance) ...253 V AC |
| Supply Voltage            | 230 V   |
| Rated Frequency (f)       | 50 ... 60 Hz  |
| Maximum Load Capacity     | Resistive load 16 A<br>Inductive Load 4 A                                   |

|                         |  |
|-------------------------|--|
| Maximum Switching Power | 4000 W<br>Incandescent Lamp or Halogen High Voltage Lamps 2500 W<br>Fluorescent Lamp 1200 W<br>Low Voltage Halogen Lamp 2000 W<br>Low Consumption Lamp (CFL) 2500 W<br>LED 900 W |
|                         | 0.5 W  |
| Power Loss              | 0.5 W  |
| Power Supply            | (-15%..+10%) 230 V AC  |
| Accuracy                | Operating accuracy: ± 1 second/day at 23°C<br>Switching accuracy: ± 5 minutes  |
| Number of Channels      | 1  |
| Tightening Torque       | 0.3 N·m  |
| Minimum Switching Time  | 15 minute [unit of time]   |
| Contact Type            | Normally Open (NO)   |
| Meter Type              | Electromechanical  |
| Mounting Type           | DIN-Rail   |
| Number of Batteries     | 0  |
| Connecting Capacity     | Solid 4 mm²  |
| Terminal Type           | Captive Screw  |

Material Compliance

|   |                                   |
|---|-----------------------------------|
| RoHS Information                            | 2CSC441017D2701                   |
| RoHS Status                                 | Following EU Directive 2011/65/EU |
| RoHS Date                                   | 20211115                          |
| REACH Declaration                           | 9AKK108467A9482                   |
| Conflict Minerals Reporting Template (CMRT) | 9AKK108468A3363                   |

Environmental

|                         |  |
|-------------------------|--|
| Ambient Air Temperature | Operation -10 ... 45 °C<br>Storage -20 ... 60 °C |
| Degree of Protection    | Housing IP20                                     |

Dimensions

|                                     |                 |
|-------------------------------------|-----------------|
| Width in Number of Modular Spacings | 1               |
| Product Net Width                   | 17.5 mm         |
| Product Net Height                  | 66 mm           |
| Product Net Depth / Length          | 90 mm           |
| Product Net Weight                  | 0.072 kg        |
| Dimension Diagram                   | 9AKK107992A8050 |

Ordering

|                              |             |
|------------------------------|-------------|
| Package Level 1 Units        | box 1 piece |
| Package Level 1 Gross Weight | 0.085 kg    |
| E-Number (Sweden)            | 1330661     |

| Certificates and Declarations  |                 |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 2CSC441017D2701 |

| Installation             |                 |
|--------------------------|-----------------|
| Instructions and Manuals | 2CSM441039D5601 |

| Popular Downloads                 |                 |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 9AKK107991A8329 |

| Classifications            |  |
|----------------------------|--|
| ETIM 8                     | EC002304 - Analogous time switch for distribution board    |
| ETIM 9                     | EC002304 - Analogous time switch for distribution board    |
| WEEE Category              | 5. Small Equipment (No External Dimension More Than 50 cm) |
| WEEE B2C / B2B             | Business To Consumer                                       |
| CN8                        | 85364900   |
| eClass                     | V11.0 : 27200109   |
| Object Classification Code | K  |

| Categories   |  |
|--|--|
| Low Voltage Products and Systems → Modular DIN Rail Products → Control and Automation Devices → Analogue and Digital Time Switches |  |

