AD1NO-R-15m 1/4



PRODUCT-DETAILS

AD1NO-R-15m

AD1NO-R-15m Analog Time switch



General Information	
Extended Product Type	AD1NO-R-15m
Product ID	2CSM222461R1000
EAN	8012542224617
Catalog Description	AD1NO-R-15m Analog Time switch
Long Description	Analog time switch, daily proramming, 1 channel NO, 15 minutes switch, with reserve

Technical	
Standards	EN 60730-2-7
Function	Daily
Rated Operational Voltage	230 V
Operational Voltage	Maximum (Incl. Tolerance) 195 V AC Maximum (Incl. Tolerance)253 V AC
Supply Voltage	230 V
Rated Frequency (f)	50 60 Hz
Maximum Load Capacity	Resistive load 16 A Inductive Load 4 A

AD1NO-R-15m 2/4

Maximum Switching 4000 W Power Incandescent Lamp or Halogen High Voltage Lamps 2500 W Fluorescent Lamp 1200 W Low Voltage Halogen Lamp 2000 W Low Consumption Lamp (CFL) 2500 W **LED 900 W** 0.5 W Power Loss **Power Supply** (-15%..+10%) 230 V AC Operating accuracy: $\pm\,1\,\text{second/day}$ at 23°C Accuracy Switching accuracy: ± 5 minutes **Number of Channels Tightening Torque** 0.3 N·m Minimum Switching 15 minute [unit of time] Normally Open (NO) Contact Type Meter Type Electromechanical DIN-Rail Mounting Type Options Provided With running reserve Nickel-Metal Hydride **Battery Chemical** Composition 100 hour **Battery Life Battery Type Button Cell Battery Weight** 0.004 kg Number of Batteries Solid 4 mm² **Connecting Capacity** Terminal Type Captive Screw

	Mater	ial	Com	pliance
--	-------	-----	-----	---------

RoHS Information	2CSC441017D2701
RoHS Status	Following EU Directive 2011/65/EU
RoHS Date	20211115
REACH Declaration	9AKK108467A9482
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Environmental

Ambient Air	Operation -10 45 °C
Temperature	Storage -20 60 °C
Degree of Protection	Housing IP20

Dimensions Width in Number of Modular Spacings Product Net Width 17.5 mm Product Net Height 66 mm Product Net Depth / Length

Product Net Weight 0.075 kg
Dimension Diagram 9AKK107992A8050

AD1NO-R-15m 3/4

Ordering	
Package Level 1 Units	box 1 piece
Package Level 1 Gross Weight	0.088 kg
E-Number (Sweden)	1330662

Certificates and Declarations	

Declaration of 2CSC441017D2701
Conformity - CE

Installation Instructions and 2CSM441039D5601 Manuals

Popular Downloads	
Data Sheet, Technical	9AKK107991A8329
Information	

Classifications	
ETIM 8	EC002304 - Analogous time switch for distribution board
ETIM 9	EC002304 - Analogous time switch for distribution board
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	85364900
eClass	V11.0 : 27200109
Object Classification Code	К

Categories

 $Low\ Voltage\ Products\ \rightarrow\ Modular\ DIN\ Rail\ Products\ \rightarrow\ Control\ and\ Automation\ Devices\ \rightarrow\ Analogue\ and\ Digital\ Time\ Switches$

AD1NO-R-15m 4/4









360