



PRODUCT-DETAILS

# AF09Z-30-01-30

## AF09Z-30-01-30 24VDC Contactor



| General Information   |  |
|-----------------------|--|
| Extended Product Type | AF09Z-30-01-30   |
| Product ID            | 1SBL136001R3001  |
| EAN                   | 3471523113398  |
| Catalog Description   | AF09Z-30-01-30 24VDC Contactor   |
| Long Description      | The AF09Z-30-01-30 is a 3-pole - 690 V IEC or 600 UL contactor with one built-in auxiliary contact and screw terminals, controlling motors up to 4 kW / 400 V AC (AC-3) or 5 hp / 480 V UL and switching power circuits up to 25 A (AC-1) or 25 A UL general use. Thanks to the AF technology, the contactor has a 24 V DC coil, featuring a reduced holding coil consumption down to 1.7 W and offering the possibility of a direct control by PLC-output $\geq 250$ mA 24 V DC, without need of additional interface relay, reducing panel energy consumptions and ensuring distinct operations in unstable networks. Furthermore, surge protection is built-in, offering a compact solution. AF contactors have a block type design, can be easily extended with add-on auxiliary contact blocks and an additional wide range of accessories. |

| Ordering               |          |
|------------------------|----------|
| Minimum Order Quantity | 1 piece  |
| Customs Tariff Number  | 85364900 |

Popular Downloads

|                          |                 |
|--------------------------|-----------------|
| Instructions and Manuals | 1SBC101053M6801 |
| CAD Dimensional Drawing  | 2CDC001079B0201 |

Dimensions

|                            |         |
|----------------------------|---------|
| Product Net Width          | 45 mm   |
| Product Net Depth / Length | 97 mm   |
| Product Net Height         | 86 mm   |
| Product Net Weight         | 0.43 kg |

Technical

|  |  |
|--|--|
| Number of Main Contacts NO                               | 3  |
| Number of Main Contacts NC                               | 0  |
| Number of Auxiliary Contacts NO                          | 0  |
| Number of Auxiliary Contacts NC                          | 1  |
| Standards  | IEC/EN 60947-1, IEC/EN 60947-4-1, UL 60947-4-1, CSA C22.2 No. 60947-4-1  |
| Rated Operational Voltage                                | Auxiliary Circuit 690 V<br>Main Circuit 690 V  |
| Rated Frequency (f)                                      | Auxiliary Circuit 50 / 60 Hz<br>Main Circuit 50 / 60 Hz  |
| Conventional Free-air Thermal Current (I <sub>th</sub> ) | acc. to IEC 60947-4-1, Open Contactors $\Theta = 40\text{ }^{\circ}\text{C}$ 35 A<br>acc. to IEC 60947-5-1, $\Theta = 40\text{ }^{\circ}\text{C}$ 16 A |
| Rated Operational Current AC-1 (I <sub>e</sub> )         | (690 V) 40 °C 25 A<br>(690 V) 60 °C 25 A<br>(690 V) 70 °C 22 A   |
| Rated Operational Current AC-3 (I <sub>e</sub> )         | (415 V) 60 °C 9 A<br>(440 V) 60 °C 9 A<br>(500 V) 60 °C 9.5 A<br>(690 V) 60 °C 7 A<br>(380 / 400 V) 60 °C 9 A<br>(220 / 230 / 240 V) 60 °C 9 A         |
| Rated Operational Current AC-3e (I <sub>e</sub> )        | (415 V) 60 °C 9 A<br>(440 V) 60 °C 9 A<br>(500 V) 60 °C 9.5 A<br>(690 V) 60 °C 7 A<br>(380 / 400 V) 60 °C 9 A<br>(220 / 230 / 240 V) 60 °C 9 A         |
| Rated Operational Power AC-3 (P <sub>e</sub> )           | (415 V) 4 kW<br>(440 V) 4 kW<br>(500 V) 5.5 kW<br>(690 V) 5.5 kW<br>(380 / 400 V) 4 kW<br>(220 / 230 / 240 V) 2.2 kW                                   |
| Rated Operational Power AC-3e (P <sub>e</sub> )          | (415 V) 4 kW<br>(440 V) 4 kW<br>(500 V) 5.5 kW<br>(690 V) 5.5 kW<br>(380 / 400 V) 4 kW<br>(220 / 230 / 240 V) 2.2 kW                                   |
| Rated Operational Current AC-15 (I <sub>e</sub> )        | (500 V) 2 A<br>(690 V) 2 A   |

|   |   |
|---|---|
|   | (24 / 127 V) 6 A<br>(220 / 240 V) 4 A<br>(400 / 440 V) 3 A  |
| Rated Short-time<br>Withstand Current Low<br>Voltage ( $I_{cw}$ ) | at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 150 A<br>at 40 °C Ambient Temp, in Free Air, from a Cold State 15 min 35 A<br>at 40 °C Ambient Temp, in Free Air, from a Cold State 1 min 60 A<br>at 40 °C Ambient Temp, in Free Air, from a Cold State 1 s 300 A<br>at 40 °C Ambient Temp, in Free Air, from a Cold State 30 s 80 A<br>for 0.1 s 140 A<br>for 1 s 100 A   |
| Maximum Breaking<br>Capacity                                      | $\cos \phi = 0.45$ ( $\cos \phi = 0.35$ for $I_e > 100$ A) at 440 V 250 A<br>$\cos \phi = 0.45$ ( $\cos \phi = 0.35$ for $I_e > 100$ A) at 690 V 106 A  |
| Maximum Electrical<br>Switching Frequency                         | (AC-1) 600 cycles per hour<br>(AC-15) 1200 cycles per hour<br>(AC-2 / AC-4) 300 cycles per hour<br>(AC-3) 1200 cycles per hour<br>(DC-13) 900 cycles per hour   |
| Rated Operational<br>Current DC-1 ( $I_e$ )                       | (110 V) 1-Pole, 40 °C 10 A<br>(110 V) 1-Pole, 60 °C 10 A<br>(110 V) 1-Pole, 70 °C 10 A<br>(110 V) 2 Poles in Series, 40 °C 25 A<br>(110 V) 2 Poles in Series, 60 °C 25 A<br>(110 V) 2 Poles in Series, 70 °C 22 A<br>(110 V) 3 Poles in Series, 40 °C 25 A<br>(110 V) 3 Poles in Series, 60 °C 25 A<br>(110 V) 3 Poles in Series, 70 °C 22 A<br>(220 V) 2 Poles in Series, 40 °C 10 A<br>(220 V) 2 Poles in Series, 60 °C 10 A<br>(220 V) 2 Poles in Series, 70 °C 10 A<br>(220 V) 3 Poles in Series, 40 °C 25 A<br>(220 V) 3 Poles in Series, 60 °C 25 A<br>(220 V) 3 Poles in Series, 70 °C 22 A<br>(72 V) 1-Pole, 40 °C 25 A<br>(72 V) 1-Pole, 60 °C 25 A<br>(72 V) 1-Pole, 70 °C 22 A<br>(72 V) 2 Poles in Series, 40 °C 25 A<br>(72 V) 2 Poles in Series, 60 °C 25 A<br>(72 V) 2 Poles in Series, 70 °C 22 A<br>(72 V) 3 Poles in Series, 40 °C 25 A<br>(72 V) 3 Poles in Series, 60 °C 25 A<br>(72 V) 3 Poles in Series, 70 °C 22 A |
| Rated Operational<br>Current DC-3 ( $I_e$ )                       | (110 V) 1-Pole, 40 °C 6 A<br>(110 V) 1-Pole, 60 °C 6 A<br>(110 V) 1-Pole, 70 °C 6 A<br>(110 V) 2 Poles in Series, 40 °C 25 A<br>(110 V) 2 Poles in Series, 60 °C 25 A<br>(110 V) 2 Poles in Series, 70 °C 22 A<br>(110 V) 3 Poles in Series, 40 °C 25 A<br>(110 V) 3 Poles in Series, 60 °C 25 A<br>(110 V) 3 Poles in Series, 70 °C 22 A<br>(220 V) 2 Poles in Series, 40 °C 6 A<br>(220 V) 2 Poles in Series, 60 °C 6 A<br>(220 V) 2 Poles in Series, 70 °C 6 A<br>(220 V) 3 Poles in Series, 40 °C 25 A<br>(220 V) 3 Poles in Series, 60 °C 25 A<br>(220 V) 3 Poles in Series, 70 °C 22 A<br>(72 V) 1-Pole, 40 °C 25 A<br>(72 V) 1-Pole, 60 °C 25 A<br>(72 V) 1-Pole, 70 °C 22 A<br>(72 V) 2 Poles in Series, 40 °C 25 A<br>(72 V) 2 Poles in Series, 60 °C 25 A<br>(72 V) 2 Poles in Series, 70 °C 22 A<br>(72 V) 3 Poles in Series, 40 °C 25 A<br>(72 V) 3 Poles in Series, 60 °C 25 A<br>(72 V) 3 Poles in Series, 70 °C 22 A       |
| Rated Operational<br>Current DC-5 ( $I_e$ )                       | (110 V) 1-Pole, 40 °C 4 A<br>(110 V) 1-Pole, 60 °C 4 A<br>(110 V) 1-Pole, 70 °C 4 A<br>(110 V) 2 Poles in Series, 40 °C 10 A<br>(110 V) 2 Poles in Series, 60 °C 10 A   |

|   |  |
|---|--|
|   | (110 V) 2 Poles in Series, 70 °C 10 A<br>(110 V) 3 Poles in Series, 40 °C 25 A<br>(110 V) 3 Poles in Series, 60 °C 25 A<br>(110 V) 3 Poles in Series, 70 °C 22 A<br>(220 V) 2 Poles in Series, 40 °C 4 A<br>(220 V) 2 Poles in Series, 60 °C 4 A<br>(220 V) 2 Poles in Series, 70 °C 4 A<br>(220 V) 3 Poles in Series, 40 °C 9 A<br>(220 V) 3 Poles in Series, 60 °C 9 A<br>(220 V) 3 Poles in Series, 70 °C 9 A<br>(72 V) 1-Pole, 40 °C 9 A<br>(72 V) 1-Pole, 60 °C 9 A<br>(72 V) 1-Pole, 70 °C 9 A<br>(72 V) 2 Poles in Series, 40 °C 25 A<br>(72 V) 2 Poles in Series, 60 °C 25 A<br>(72 V) 2 Poles in Series, 70 °C 22 A<br>(72 V) 3 Poles in Series, 40 °C 25 A<br>(72 V) 3 Poles in Series, 60 °C 25 A<br>(72 V) 3 Poles in Series, 70 °C 22 A |
| Rated Operational Current DC-13 ( $I_e$ )     | (24 V) 6 A / 144 W<br>(48 V) 2.8 A / 134 W<br>(72 V) 1 A / 72 W<br>(110 V) 0.55 A / 60 W<br>(125 V) 0.55 A / 69 W<br>(220 V) 0.27 A / 60 W<br>(250 V) 0.27 A / 68 W<br>(400 V) 0.15 A / 60 W<br>(500 V) 0.13 A / 65 W<br>(600 V) 0.1 A / 60 W  |
| Rated Insulation Voltage ( $U_i$ )            | acc. to IEC 60947-4-1 690 V<br>acc. to IEC 60947-5-1 690 V<br>acc. to UL/CSA 600 V   |
| Rated Impulse Withstand Voltage ( $U_{imp}$ ) | 6 kV   |
| Maximum Mechanical Switching Frequency        | 3600 cycles per hour   |
| Rated Control Circuit Voltage ( $U_c$ )       | DC Operation 24 V  |
| Operate Time                                  | Between Coil De-energization and NC Contact Closing 22 ... 57 ms<br>Between Coil De-energization and NO Contact Opening 17 ... 29 ms<br>Between Coil Energization and NC Contact Opening 20 ... 35 ms<br>Between Coil Energization and NO Contact Closing 27 ... 53 ms   |
| Mounting on DIN Rail                          | TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715<br>TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715   |
| Mounting by Screws (not supplied)             | 2 x M4 screws placed diagonally  |
| Connecting Capacity Main Circuit              | Flexible with Ferrule 1/2x 0.75 ... 6 mm <sup>2</sup><br>Flexible with Insulated Ferrule 1x 0.75 ... 4 mm <sup>2</sup><br>Flexible with Insulated Ferrule 2x 0.75 ... 2.5 mm <sup>2</sup><br>Rigid Solid 1/2x 1 ... 4 mm <sup>2</sup><br>Rigid Stranded 1/2x 1 ... 6 mm <sup>2</sup>   |
| Connecting Capacity Auxiliary Circuit         | Flexible with Ferrule 1/2x 0.75 ... 2.5 mm <sup>2</sup><br>Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm <sup>2</sup><br>Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm <sup>2</sup><br>Rigid Solid 1/2x 1 ... 2.5 mm <sup>2</sup><br>Rigid Stranded 1/2x 1 ... 2.5 mm <sup>2</sup>   |
| Connecting Capacity Control Circuit           | Flexible with Ferrule 1/2x 0.75 ... 2.5 mm <sup>2</sup><br>Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm <sup>2</sup><br>Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm <sup>2</sup><br>Rigid Solid 1/2x 1 ... 2.5 mm <sup>2</sup><br>Rigid Stranded 1/2x 1 ... 2.5 mm <sup>2</sup>   |
| Wire Stripping Length                         | Auxiliary Circuit 10 mm<br>Control Circuit 10 mm<br>Main Circuit 10 mm   |
| Degree of Protection                          | acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP20<br>acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20  |

acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20

|               |                 |
|---------------|-----------------|
| Terminal Type | Screw Terminals |
|---------------|-----------------|

Technical UL/CSA

|  |  |
|--|--|
| NEMA Size                                    | 00   |
| Continuous Current Rating NEMA               | 9 A  |
| Horsepower Rating NEMA                       | (115 V AC) Single Phase 1/3 Hp<br>(200 V AC) Three Phase 1-1/2 Hp<br>(230 V AC) Single Phase 1 Hp<br>(230 V AC) Three Phase 1-1/2 Hp<br>(460 V AC) Three Phase 2 Hp<br>(575 V AC) Three Phase 2 Hp                                 |
| Maximum Operating Voltage UL/CSA             | Main Circuit 600 V   |
| General Use Rating UL/CSA                    | (600 V AC) 25 A  |
| Horsepower Rating UL/CSA                     | (120 V AC) Single Phase 3/4 hp<br>(200 ... 208 V AC) Three Phase 2 hp<br>(220 ... 240 V AC) Three Phase 2 hp<br>(240 V AC) Single Phase 1-1/2 hp<br>(440 ... 480 V AC) Three Phase 5 hp<br>(550 ... 600 V AC) Three Phase 7-1/2 hp |
| Connecting Capacity Main Circuit UL/CSA      | Rigid Solid 1/2x 16-10 AWG<br>Rigid Stranded 1/2x 16-10 AWG  |
| Connecting Capacity Auxiliary Circuit UL/CSA | Rigid Solid 1/2x 18-14 AWG<br>Rigid Stranded 1/2x 18-14 AWG  |
| Connecting Capacity Control Circuit UL/CSA   | Rigid Solid 1/2x 18-14 AWG<br>Rigid Stranded 1/2x 18-14 AWG  |
| Tightening Torque UL/CSA                     | Auxiliary Circuit 11 in-lb<br>Control Circuit 11 in-lb<br>Main Circuit 13 in-lb  |

Environmental

|  |   |
|--|---|
| Ambient Air Temperature                | Close to Contactor Fitted with Thermal O/L Relay -25 ... 60 °C<br>Close to Contactor without Thermal O/L Relay -40 ... 70 °C<br>Close to Contactor for Storage -60 ... +80 °C |
| Climatic Withstand                     | Category B according to IEC 60947-1 Annex Q   |
| Maximum Operating Altitude Permissible | Without Derating 3000 m   |
| Resistance to Vibrations               | 4g Closed Position & 2g Open position 5 ... 300 Hz  |

Material Compliance

|   |  |
|---|--|
| Conflict Minerals Reporting Template (CMRT) | 9AKK108467A5658  |
| REACH Declaration                           | 2CMT2021-006202  |
| RoHS Information                            | 2CMT2021-006277  |
| RoHS Status                                 | Following EU Directive 2011/65/EU                          |
| Toxic Substances Control Act - TSCA         | 2CMT2023-006525  |
| WEEE B2C / B2B                              | Business To Business                                       |
| WEEE Category                               | 5. Small Equipment (No External Dimension More Than 50 cm) |

| Certificates and Declarations       |  |
|-------------------------------------|--|
| ABS Certificate                     | ABS_20-2060694-PDA                         |
| CB Certificate                      | CB_SE-108879                               |
| CCC Certificate                     | CCC_2010010304445624                       |
| CQC Certificate                     | CQC2010010304445624<br>CQC2020010304298240 |
| Declaration of<br>Conformity - CCC  | 2020980304001253<br>2020980304001082       |
| Declaration of<br>Conformity - CE   | 1SBD250000U1000                            |
| Declaration of<br>Conformity - UKCA | 1SBD250031U1000                            |
| DNV Certificate                     | DNV_TAE00001AF-4                           |
| EAC Certificate                     | EAC_RU_FRME77B03447                        |
| RINA Certificate                    | RINA_ELE240318XG                           |
| RMRS Certificate                    | RMRS_1802705280                            |
| UL Certificate                      | UL-US-2150887-5<br>UL-CA-2142658-5         |

| Container Information             |                |
|-----------------------------------|----------------|
| Package Level 1 Units             | box 1 piece    |
| Package Level 1 Width             | 96 mm          |
| Package Level 1 Depth /<br>Length | 112 mm         |
| Package Level 1 Height            | 50 mm          |
| Package Level 1 Gross<br>Weight   | 0.475 kg       |
| Package Level 1 EAN               | 3471523113398  |
| Package Level 2 Units             | crate 12 piece |
| Package Level 2 Width             | 51 mm          |
| Package Level 2 Depth /<br>Length | 98 mm          |
| Package Level 2 Height            | 114 mm         |
| Package Level 2 Gross<br>Weight   | 5.7 kg         |
| Package Level 3 Units             | 576 piece      |

| Classifications                       |   |
|---------------------------------------|---|
| Object Classification<br>Code         | Q   |
| ETIM 4                                | EC000066 - Magnet contactor, AC-switching |
| ETIM 5                                | EC000066 - Magnet contactor, AC-switching |
| ETIM 6                                | EC000066 - Power contactor, AC switching  |
| ETIM 7                                | EC000066 - Power contactor, AC switching  |
| ETIM 8                                | EC000066 - Power contactor, AC switching  |
| eClass                                | V11.0 : 27371003                          |
| UNSPSC                                | 39121529                                  |
| IDEA Granular Category<br>Code (IGCC) | 4758 >> lec Contactors                    |
| E-Number (Finland)                    | 3709055                                   |

---

## Categories

---

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors → AF Contactors → AF09

