



 PRODUCT-DETAILS

AFS460-30-12-69

AFS460-30-12-69



General Information

Extended Product Type	AFS460-30-12-69
Product ID	1SFL597081R6912
EAN	7320500540886
Catalog Description	AFS460-30-12-69

Long Description	<p>The AFS460-30-12-69 is a 3 pole - 1000 V IEC or 600 V UL contactor with pre-mounted 1 left (1 N.O + 1 N.C.) and fixed 1 right (1 N.C.) side mounted auxiliary contact blocks with Main Circuit Bars connections, controlling motors up to 250 kW / 400 V AC (AC-3) or 400 hp / 480 V UL and switching power circuits up to 700 A (AC-1) or 650 A UL general use. AFS contactors can be easily integrated in machine manufacturer's systems complying with main standards EN ISO 13849 and EN 62061 - guaranteeing the safe use of your machinery and equipment. An easily identifiable yellow low energy auxiliary contact block ensures the status feedback circuits required in machine safety applications. Thanks to the AF technology, the contactor has a wide control voltage range (48-130 V 50/60 Hz and DC), managing large control voltage variations, reducing panel energy consumptions and ensuring distinct operations in unstable networks. Furthermore, surge protection is built-in, offering a compact solution. AF contactors have a block type design, can be easily extended with add-on auxiliary contact blocks and an additional wide range of accessories.</p>
------------------	---

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85364900

Popular Downloads

Data Sheet, Technical Information	1SBC100208C02__
Instructions and Manuals	1SFC380023-en
CAD Dimensional Drawing	2CDC001079B0201

Dimensions

Product Net Width	186 mm
Product Net Depth / Length	216 mm
Product Net Height	278 mm
Product Net Weight	10.6 kg

Technical

Number of Main Contacts NO	3
Number of Main Contacts NC	0
Number of Auxiliary Contacts NO	1
Number of Auxiliary Contacts NC	2
Rated Operational Voltage	Main Circuit 1000 V
Rated Frequency (f)	Main Circuit 50 / 60 Hz
Conventional Free-air Thermal Current (I _{th})	acc. to IEC 60947-4-1, Open Contactors $\Theta = 40\text{ °C}$ 700 A
Rated Operational Current AC-1 (I _e)	(1000 V) 40 °C 700 A (1000 V) 55 °C 600 A (1000 V) 70 °C 480 A (690 V) 40 °C 700 A (690 V) 55 °C 600 A (690 V) 70 °C 480 A
Rated Operational Current AC-3 (I _e)	(415 V) 55 °C 460 A (440 V) 55 °C 460 A (500 V) 55 °C 460 A (690 V) 55 °C 400 A (1000 V) 55 °C 200 A (380 / 400 V) 55 °C 460 A (220 / 230 / 240 V) 55 °C 460 A
Rated Operational Power AC-3 (P _e)	(415 V) 250 kW (440 V) 250 kW (500 V) 315 kW (690 V) 355 kW (1000 V) 280 kW (380 / 400 V) 250 kW (220 / 230 / 240 V) 132 kW
Rated Breaking Capacity AC-3	8 x I _e AC-3
Rated Making Capacity AC-3	10 x I _e AC-3

Short-Circuit Protective Devices	gG Type Fuses 800 A
Rated Short-time Withstand Current Low Voltage (I_{cw})	at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 4400 A at 40 °C Ambient Temp, in Free Air, from a Cold State 15 min 840 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 min 2500 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 s 4600 A at 40 °C Ambient Temp, in Free Air, from a Cold State 30 s 3100 A
Maximum Breaking Capacity	cos phi=0.45 (cos phi=0.35 for $I_e > 100$ A) at 440 V 5000 A cos phi=0.45 (cos phi=0.35 for $I_e > 100$ A) at 690 V 4500 A
Maximum Electrical Switching Frequency	(AC-1) 300 cycles per hour (AC-2 / AC-4) 60 cycles per hour (AC-3) 300 cycles per hour
Rated Operational Current DC-1 (I_e)	(110 V) 1-Pole, 40 °C 700 A (110 V) 2 Poles in Series, 40 °C 700 A (220 V) 3 Poles in Series, 40 °C 600 A (600 V) 3 Poles in Series, 40 °C 700 A
Rated Operational Current DC-3 (I_e)	(110 V) 1-Pole, 40 °C 700 A (110 V) 2 Poles in Series, 40 °C 700 A (220 V) 3 Poles in Series, 40 °C 600 A (600 V) 3 Poles in Series, 40 °C 700 A
Rated Operational Current DC-5 (I_e)	(110 V) 1-Pole, 40 °C 700 A (110 V) 2 Poles in Series, 40 °C 700 A (220 V) 3 Poles in Series, 40 °C 600 A (600 V) 3 Poles in Series, 40 °C 700 A
Rated Insulation Voltage (U_i)	acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 1000 V acc. to UL/CSA 600 V
Rated Impulse Withstand Voltage (U_{imp})	Main Circuit 8 kV
Mechanical Durability	5 million
Maximum Mechanical Switching Frequency	300 cycles per hour
Coil Operating Limits	(acc. to IEC 60947-4-1) 0.85 x U_c Min. ... 1.1 x U_c Max. (at $\theta \leq 70$ °C)
Rated Control Circuit Voltage (U_c)	50 Hz 48 ... 130 V 60 Hz 48 ... 130 V DC Operation 48 ... 130 V
Coil Consumption	Holding at Max. Rated Control Circuit Voltage 50 Hz 12 V·A Holding at Max. Rated Control Circuit Voltage 60 Hz 12 V·A Holding at Max. Rated Control Circuit Voltage DC 7.5 V·A Pull-in at Max. Rated Control Circuit Voltage 50 Hz 1215 V·A Pull-in at Max. Rated Control Circuit Voltage 60 Hz 1215 V·A Pull-in at Max. Rated Control Circuit Voltage DC 1150 V·A
Operate Time	Between Coil De-energization and NC Contact Closing 45 ... 55 ms Between Coil De-energization and NO Contact Opening 48 ... 58 ms Between Coil Energization and NC Contact Opening 45 ... 115 ms Between Coil Energization and NO Contact Closing 50 ... 120 ms
Connecting Capacity Main Circuit	Bar 47 mm ² Rigid Al-Cable 2x240 mm ² Rigid Cu-Cable 240 mm ²
Connecting Capacity Auxiliary Circuit	Flexible with Ferrule 2x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm ² Flexible 2x0.75 ... 2.5 mm ² Solid 2 x 1 ... 4 mm ² Stranded 2 x 1 ... 4 mm ²
Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP00
Terminal Type	Main Circuit: Bars

Technical UL/CSA

NEMA Size	6
Maximum Operating Voltage UL/CSA	Main Circuit 600 V

General Use Rating UL/CSA	(600 V AC) 650 A
Horsepower Rating UL/CSA	(200 ... 208 V AC) Three Phase 150 hp (220 ... 240 V AC) Three Phase 200 hp (440 ... 480 V AC) Three Phase 400 hp (550 ... 600 V AC) Three Phase 500 hp

Environmental

Ambient Air Temperature	Close to Contactor Fitted with Thermal O/L Relay (0.85 ... 1.1 Uc) -25 ... 50 °C Close to Contactor without Thermal O/L Relay (0.85 ... 1.1 Uc) -40 ... 70 °C Close to Contactor for Storage -40 ... 70 °C
Maximum Operating Altitude Permissible	Without Derating 3000 m

Material Compliance

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	2CMT2021-006202
RoHS Information	2CMT2021-006277
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA	2CMT2023-006525
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Circular Value

ABB EcoSolutions	Yes
Circular Design Principles Recyclability Rate	Design for Closing Resource Loops - Standard EN45555 - 63.1 %
Group Waste to Landfill Target	Non-hazardous waste is sent to a landfill, where there is no alternative option available within 100km of a facility
Improved Resource Efficiency for Customers	Product Efficiency - Product considered more energy-efficient compared to similar product on market or older products from the same line
Sustainable Material Content	Recycled Metal - 37 %

Eco Transparency

Environmental Product Declaration - EPD	1SFC100105D0201
--	-----------------

Certificates and Declarations

CB Certificate	SE-82316
CQC Certificate	CQC2007010304256683
cUL Certificate	20121207-E36588
Declaration of Conformity - CCC	2020980304001300
Declaration of Conformity - CE	2CMT2018-005695

Declaration of Conformity - UKCA	2CMT2020-006125
EAC Certificate	1SFC101360D1101
SUVA Certificate	2CMT2019-005859

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	280 mm
Package Level 1 Depth / Length	375 mm
Package Level 1 Height	310 mm
Package Level 1 Gross Weight	12 kg
Package Level 1 EAN	7320500540886

Classifications

Object Classification Code	Q
ETIM 4	EC000066 - Magnet contactor, AC-switching
ETIM 5	EC000066 - Magnet contactor, AC-switching
ETIM 6	EC000066 - Power contactor, AC switching
ETIM 7	EC000066 - Power contactor, AC switching
ETIM 8	EC000066 - Power contactor, AC switching
eClass	V11.0 : 27371003
UNSPSC	39121529
IDEA Granular Category Code (IGCC)	4755 >> Contactors
E-Number (Finland)	3709042

Accessories

Identifier	Description	Type	Quantity	Unit Of Measure
1SFN010716R1010	CEL18-10 Auxiliary Contact Block	CEL18-10	1	piece
1SFN010716R1001	CEL18-01 Auxiliary Contact Block	CEL18-01	1	piece
1SFN010720R1011	CAL18-11 Auxiliary Contact Block	CAL18-11	1	piece
1SFN125703R1000	LT460-AL Terminal shroud	LT460-AL	1	piece
1SFN125701R1000	LT460-AC Terminal shroud	LT460-AC	1	piece
1SFN075710R1000	LX460 Terminal Extension	LX460	1	piece
1SFN075707R1000	LW460 Terminal Enlargement	LW460	1	piece
1SFN075703R1000	LY460 Connecting Strip	LY460	1	piece
1SFN126103R1000	LT750-AL Terminal shroud	LT750-AL	1	piece
1SFN126101R1000	LT750-AC Terminal shroud	LT750-AC	1	piece
1SFN076110R1000	LX750 Terminal Extension	LX750	1	piece
1SFN076107R1000	LW750 Terminal Enlargement	LW750	1	piece
1SFN076103R1000	LY750 Connecting Strip	LY750	1	piece

Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors → AFS Contactors → AFS460

