B21 312-100 1/4



PRODUCT-DETAILS

B21 312-100 B21 312-100, Energy meter'Silver', Modbus RS485, Single-phase, 5 A



General Information	
Extended Product Type	B21 312-100
Product ID	2CMA100155R1000
ABB Type Designation	B21 312-100
EAN	7392696001557
Catalog Description	B21 312-100, Energy meter'Silver', Modbus RS485, Single-phase, 5 A
Long Description	Advanced compact DIN-rail meter with an easy to read back lighted display. The meter is intended for use in the commercial or residential buildings etc. The meter can be used in 3 or 4 wire systems. The meter has several instrumentation values, 25 possible alarms and event logs. Single phase direct connected for active and reactive energy. Import and export of energy in different registers and one total. Resettable register for intermediate values. Up to four tariffs. Two outputs and inputs for pulses or alarm etc. RS-485 communication over Modbus RTU or EQ Bus. Accuracy class 1.0 (or B for MID meters). The meters is IEC approved + MID approved and verified.

Eco Transparency	
Environmental Product Declaration - EPD	9AKK108467A4138

B21 312-100 2/4

Standards	IEC 62053-2
Function	Electricity mete
Sub-Function	Silve
Rated Voltage (U _r)	220-240
Voltage Range	176276
Rated Current (I _n)	5 / Maximum 65 /
Current Rating	5 /
Rated Frequency (f)	50 / 60 H
	0.414 V
Communication Interface	Modbus RS48
Accuracy	Active Energy Class B MID (±1%
Measuring Instrument Conformity	Measurement Instrument Directive (MID
Meter Tariff Control	Externa
Meter Tariff Rating	Multi-Tarit
Pulse Output Rate	1-999999
Number of Poles	
Number of Phases	Single-phase
Number of Counter Positions	
Number of Digital In/Outputs	2 DI 2 DO
Meter Type	Direct connected
Mounting Type	DIN-Ra
Pulse Output Type	Electrica
Type of Indicator	Digita
Enclosure Material	Polycarbonate in transparent front glass. Glass reinforced polycarbonate in bottom case and upper case. Polycarbonate in terminal cover
I/O Option	2 digital output, 2 digital inpu
Communication	Modbus RTU
Connecting Capacity Main Circuit	1 25 mm

Material Compliance	
RoHS Information	2CMC485005
RoHS Status	Following EU Directive 2002/95/EC August 18, 2005 and amendment
RoHS Date	2012-36
REACH Declaration	9AKK108467A9482
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Environmental	
Ambient Air Temperature	Operation -40 70 °C
Degree of Protection	IP20
Environmental Information	2CMC485004D0001

Dimensions	
Width in Number of Modular Spacings	2
Product Net Width	35 mm
Product Net Height	26.5 mm
Product Net Depth /	65 mm

B21 312-100 3/4

ı	.er	20	ıtl	h
L	.eı	IU	ıu	Ш

Product Net Weight	0.15 kg
Size	97X35X65
Dimension Diagram	2CMC485004M0201

Ordering	
Package Level 1 Units	box 1 piece
Package Level 1 Gross Weight	0.20 kg
E-Number (Finland)	6625031
E-Number (Sweden)	0900034

Certificates and Declarations	
Declaration of Conformity	2CMC485001D0001

Installation	
Instructions and Manuals	2CMC485019M0201

Popular Downloads Data Sheet, Technical 2CMC485004M0201 Information

ETIM 8	EC001506 - Kilowatt-hour meter
ETIM 9	EC001506 - Kilowatt-hour meter
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	90283011
eClass	V11.0 : 27142316
Object Classification Code	Р

Accessories				
Identifier	Description	Туре	Quantity	Unit Of Measure
2CCG000242R0001	SCU100 Control unit	SCU100	1	piece
2CDG110226R0011	QA/S3.16.1 Energy Analyzer, M-Bus, 16 Devices, MDRC	QA/S3.16.1	1	piece
2CDG110227R0011	QA/S3.64.1 Energy Analyzer, M-Bus, 64 Devices, MDRC	QA/S3.64.1	1	piece
2CDG110228R0011	QA/S4.16.1 Energy Analyzer, Modbus RTU, 16 Devices, MDRC	QA/S4.16.1	1	piece
2CDG110229R0011	QA/S4.64.1 Energy Analyzer, Modbus RTU, 64 Devices, MDRC	QA/S4.64.1	1	piece
2CDG110224R0011	QA/S1.16.1 Energy Analyzer, KNX, 16 Devices, MDRC	QA/S1.16.1	1	piece

B21 312-100 4/4

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Modular\ DIN\ Rail\ Products \rightarrow Energy\ Efficiency\ Devices \rightarrow Energy\ Meters$

