



PRODUCT-DETAILS

B23 113-100

B23 113-100, Energy meter'Steel', M-bus, Three-phase, 5 A



General Information	
Extended Product Type	B23 113-100
Product ID	2CMA100165R1000
ABB Type Designation	B23 113-100
EAN	7392696001656
Catalog Description	B23 113-100, Energy meter'Steel', M-bus, Three-phase, 5 A
Long Description	Advanced compact DIN-rail meter with an easy to read back lighted display. The meter is intended for use in the commercial or residential buildings etc. The meter can be used in 3 or 4 wire systems. The meter has several instrumentation values, 25 possible alarms and event logs. Three phase direct connected for active energy. One output for pulses or alarm etc. M-Bus communication.Accuracy class 1.0 (or B for MID meters). The meters is IEC approved + MID approved and verified.

Eco Transparency	
Environmental Product Declaration - EPD	9AKK108467A4138

Technical	
Standards	EN 50470-1
Function	Electricity meter
Sub-Function	Steel
Rated Voltage (U _r)	3x220-240 V
Voltage Range	3x176...276 V
Rated Current (I _n)	5 A
	Maximum 65 A
Current Rating	5 A
Rated Frequency (f)	50 / 60 Hz
	0.721 W
Communication Interface	M-bus
Accuracy	Active Energy Class B MID (±1%)
Measuring Instrument Conformity	Measurement Instrument Directive (MID)
Meter Tariff Rating	One-Tariff
Pulse Output Rate	1-999999
Number of Poles	4
Number of Phases	Three-phase
Number of Counter Positions	7
Number of Digital In/Outputs	1 DO
Meter Type	Direct connected
Mounting Type	DIN-Rail
Pulse Output Type	Electrical
Type of Indicator	Digital
Enclosure Material	Polycarbonate in transparent front glass. Glass reinforced polycarbonate in bottom case and upper case. Polycarbonate in terminal cover.
I/O Option	1 digital output
Communication	M-Bus
Connecting Capacity Main Circuit	1 ... 25 mm²

Material Compliance	
RoHS Information	2CMC485006
RoHS Status	Following EU Directive 2002/95/EC August 18, 2005 and amendment
RoHS Date	2012-36
REACH Declaration	9AKK108467A9482
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Environmental	
Ambient Air Temperature	Operation -40 ... 70 °C
Degree of Protection	IP20
Environmental Information	2CMC485003D0001

Dimensions	
Width in Number of Modular Spacings	4
Product Net Width	70 mm
Product Net Height	26.5 mm
Product Net Depth / Length	65 mm
Product Net Weight	0.33 kg
Size	96X70X65
Dimension Diagram	2CMC485003M0201

Ordering	
Package Level 1 Units	box 1 piece
Package Level 1 Gross Weight	0.41 kg
E-Number (Finland)	6625035
E-Number (Sweden)	0900038

Certificates and Declarations	
Declaration of Conformity - CE	2CMC485001D0001

Installation	
Instructions and Manuals	2CMC485019M0201

Popular Downloads	
Data Sheet, Technical Information	2CMC485003M0201

Classifications	
ETIM 8	EC001506 - Kilowatt-hour meter
ETIM 9	EC001506 - Kilowatt-hour meter
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	90283019
eClass	V11.0 : 27142316
Object Classification Code	P

Accessories	
-------------	--

Identifier	Description	Type	Quantity	Unit Of Measure
2CCG000242R0001	SCU100 Control unit	SCU100	1	piece
2CDG110226R0011	QA/S3.16.1 Energy Analyzer, M-Bus, 16 Devices, MDRC	QA/S3.16.1	1	piece
2CDG110227R0011	QA/S3.64.1 Energy Analyzer, M-Bus, 64 Devices, MDRC	QA/S3.64.1	1	piece
2CDG110228R0011	QA/S4.16.1 Energy Analyzer, Modbus RTU, 16 Devices, MDRC	QA/S4.16.1	1	piece
2CDG110229R0011	QA/S4.64.1 Energy Analyzer, Modbus RTU, 64 Devices, MDRC	QA/S4.64.1	1	piece
2CDG110224R0011	QA/S1.16.1 Energy Analyzer, KNX, 16 Devices, MDRC	QA/S1.16.1	1	piece

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Energy Efficiency Devices → Energy Meters

