

PRODUCT-DETAILS

DDA204 B-63/0.3 AP-R

DDA204 B-63/0.3 AP-R Residual Current Device Block



General Information	
Extended Product Type	DDA204 B-63/0.3 AP-R
Product ID	2CSB204592R3630
EAN	8012542732921
Catalog Description	DDA204 B-63/0.3 AP-R Residual Current Device Block
Long Description	The RCD block DDA200 series is suitable for assembly with MCBs S200 series and S300P. Type B is also sensitive to continuous current pulsating earth fault currents. They are used for protection in installations with electronic equipment according to EN 50178. Applications: tertiary and industrial.

Technical	
Standards	IEC/EN 61009 Ann. G IEC/EN 62423
Type of Residual Current	Туре В
Rated Voltage (U _r)	230400 V
Rated Operational Voltage	230/400 V
Rated Insulation Voltage (U _i)	500 V

DDA204 B-63/0.3 AP-R 2/4

Rated Impulse	4 kV
Withstand Voltage (U _{imp}	
)	
Rated Current (I _n)	63 A
Rated Residual Current	300 mA
Maximum Surge Current	3 kA
Leakage Current Type	В
Rated Frequency (f)	50 60 Hz
Power Loss	7.6 W
Power Supply	Arbitrary
Connection	
Electrical Endurance	10000 cycle
Number of Poles	4
Operating Characteristic	Instantaneous (APR High Immunity)
Connecting Capacity	Rigid 25 25 mm²
	Flexible 25 25 mm ²

Material Compliance	
RoHS Information	9AKK106713A5615
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS Date	20070731
REACH Declaration	9AKK108467A9482
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Environmental	
Ambient Temperature	-2555 °C
Ambient Air Temperature	Operation -2555 °C
Degree of Protection	IP2X
Resistance to Vibrations	20 Cycles with Load 0.8 In: 1g or 1mm 50 150 5 Hz
Resistance to Shock acc. to IEC 60068-2-27	25g 2 shocks 13 ms
Environmental Information	Refer to RoHS

Technical UL/CSA	
Short-Circuit Current	0.3 0.3 A
Rating (SCCR)	

Dimensions	
Product Net Width	140 mm
Product Net Height	93 mm
Product Net Depth / Length	76 mm
Product Net Weight	0.337 kg

Ordering

3/4

Package Level 1 Units	box 1 piece
Package Level 1 Gross	0.394 kg
Weight	

Certificates and Declarations

Declaration of 9AKK106713A5615 Conformity - CE

Installation

Instructions and 9AKK108467A7092 Manuals

Popular Downloads

Data Sheet, Technical 9AKK107991A8329 Information

Classifications

ETIM 8	EC002297 - Residual current circuit breaker (RCCB) module
ETIM 9	EC002297 - Residual current circuit breaker (RCCB) module
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	85363030
eClass	V11.0 : 27142210
Object Classification Code	F

Categories

 $Low\ Voltage\ Products\ and\ Systems\ \rightarrow\ Modular\ DIN\ Rail\ Products\ \rightarrow\ Residual\ Current\ Devices\ RCDs\ \rightarrow\ Residual\ Current\ Devices\ RCD\ Blocks$

DDA204 B-63/0.3 AP-R 4/4

